Printing date 07/17/2024

Reviewed on 07/17/2024

Identification	
· Product identifier	
• Trade name: <u>Potassium Hydroxide 0</u> in IPA, NIST Traceable	
• Article number: CHV002	
• Details of the supplier of the safety de • Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586	lata sheet
• Information department: Technical Coordinator Sherman Nelson shermann@aquasolu • Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666	utions.org
Hazard(s) identification	
GHS02 Flame	
Flammable Liquids 2 GHS05 Corrosion Skin Corrosion 1B	H225 Highly flammable liquid and vapor. H314 Causes severe skin burns and eye damage.
Flammable Liquids 2	
Flammable Liquids 2 GHS05 Corrosion Skin Corrosion 1B Eye Damage 1 GHS07	H314 Causes severe skin burns and eye damage. H318 Causes serious eye damage.
Flammable Liquids 2 GHS05 Corrosion Skin Corrosion 1B Eye Damage 1 GHS07 Specific Target Organ Toxicity - Sing	H314 Causes severe skin burns and eye damage.
Flammable Liquids 2 Flammable Liquids 2 GHS05 Corrosion Skin Corrosion 1B Eye Damage 1 GHS07 Specific Target Organ Toxicity - Sing. Label elements	H314 Causes severe skin burns and eye damage. H318 Causes serious eye damage.
Flammable Liquids 2 Flammable Liquids 2 GHS05 Corrosion Skin Corrosion 1B Eye Damage 1 GHS07 Specific Target Organ Toxicity - Singu- Label elements GHS label elements The product is cl	H314 Causes severe skin burns and eye damage. H318 Causes serious eye damage. le Exposure 3 H336 May cause drowsiness or dizziness.
Flammable Liquids 2 Flammable Liquids 2 GHS05 Corrosion Skin Corrosion 1B Eye Damage 1 GHS07 Specific Target Organ Toxicity - Singu- Label elements GHS label elements The product is cl Hazard pictograms Constant of the product of the pictograms Constant of the pictograms	H314 Causes severe skin burns and eye damage. H318 Causes serious eye damage. le Exposure 3 H336 May cause drowsiness or dizziness.
Flammable Liquids 2 Flammable Liquids 2 GHS05 Corrosion Skin Corrosion 1B Eye Damage 1 GHS07 Specific Target Organ Toxicity - Singu Label elements GHS label elements The product is cl Hazard pictograms GHS02 GHS05 GHS07	H314 Causes severe skin burns and eye damage. H318 Causes serious eye damage. le Exposure 3 H336 May cause drowsiness or dizziness. lassified and labeled according to the Globally Harmonized System (GHS

Printing date 07/17/2024

Reviewed on 07/17/2024

Trade name: Potassium Hydroxide 0.5N in IPA, NIST Traceable

(Contd. of page 1)
· Hazard statements
Highly flammable liquid and vapor.
Causes severe skin burns and eye damage.
May cause drowsiness or dizziness.
· Precautionary statements
Keep away from heat/sparks/open flames/hot surfaces No smoking.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe dusts or mists.
Wash thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.
If swallowed: Rinse mouth. Do NOT induce vomiting.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
Immediately call a poison center/doctor.
Specific treatment (see on this label).
Wash contaminated clothing before reuse.
In case of fire: Use CO2, powder or water spray to extinguish.
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.
· Classification system:
· NFPA ratings (scale 0 - 4)
Health = 3
$\frac{3}{Fire = 3}$
$\frac{3}{8} \frac{0}{Reactivity} = 0$
Keuchivity = 0
· HMIS-ratings (scale 0 - 4)
HEALTH 3 Health = 3
FIRE 3 Fire = 3
REACTIVITY 0 $Reactivity = 0$
· Other hazards
· Results of PBT and vPvB assessment
· PBT: Not applicable.
· vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- $\cdot \textit{Description: Mixture of the substances listed below with nonhazardous additions.}$

· Dangerous components:

CAS: 67-63-0 Isopropanol

96.498% (Contd. on page 3)

US -

Printing date 07/17/2024

Reviewed on 07/17/2024

Trade name: Potassium Hydroxide 0.5N in IPA, NIST Traceable

CAS: 1310-58-3 Potassium Hydroxide

(Contd. of page 2) 3.503%

4 First-aid measures

- · Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 *Fire-fighting measures*

- · Extinguishing media
- \cdot Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures	
Mount respiratory protective device.	
Wear protective equipment. Keep unprotected persons away.	
· Environmental precautions:	
Dilute with plenty of water.	
Do not allow to enter sewers/ surface or ground water.	
• Methods and material for containment and cleaning up:	
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).	
Use neutralizing agent.	
Dispose contaminated material as waste according to section 13.	
Ensure adequate ventilation.	
· Reference to other sections	
See Section 7 for information on safe handling.	
See Section 8 for information on personal protection equipment.	
See Section 13 for disposal information.	
· Protective Action Criteria for Chemicals	
· PAC-1:	
CAS: 67-63-0 Isopropanol	400 ppm
CAS: 1310-58-3 Potassium Hydroxide	0.18 mg/m ³
· PAC-2:	
CAS: 67-63-0 Isopropanol	2000* ppm
	(Contd. on page 4

Printing date 07/17/2024

Reviewed on 07/17/2024

Trade name: Potassium Hydroxide 0.5N in IPA, NIST Traceable

CAS: 1310-58-3	Potassium Hydroxide	(Contd. of page 3) $2 mg/m^3$
· PAC-3:		
CAS: 67-63-0	Isopropanol	12000** ppm
CAS: 1310-58-3	Potassium Hydroxide	54 mg/m ³

7 Handling and storage

· Handling:

- Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
 Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- Keep respiratory protective device available.
- \cdot Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
 Store in cool, dry conditions in well sealed receptacles.
 Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see section 7.

· Control parameters

Control parameters
· Components with limit values that require monitoring at the workplace:
CAS: 67-63-0 Isopropanol
PEL Long-term value: 980 mg/m ³ , 400 ppm
REL Short-term value: 1225 mg/m ³ , 500 ppm Long-term value: 980 mg/m ³ , 400 ppm
TLV Short-term value: 400 ppm Long-term value: 200 ppm
BEI, A4
CAS: 1310-58-3 Potassium Hydroxide
REL Ceiling limit value: 2 mg/m ³
TLV Ceiling limit value: 2 mg/m ³
· Ingredients with biological limit values:
CAS: 67-63-0 Isopropanol
BEI 40 mg/L
LD50 Intraperitoneal: urine
Time: end of shift at end of workweek
LD50: Acetone (background, nonspecific)
• Additional information: The lists that were valid during the creation were used as basis.

(Contd. on page 5)

US

Printing date 07/17/2024

Reviewed on 07/17/2024

Trade name: Potassium Hydroxide 0.5N in IPA, NIST Traceable

(Contd. of page 4)

- · Exposure controls
- · Personal protective equipment:

• General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. • Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation \cdot *Material of gloves*

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

 Information on basic physical and General Information Appearance: 	chemical properties	
Form:	Liquid	
Color:	Clear	
· Odor:	IPA	
· Odor threshold:	Not determined.	
· pH-value:	Not determined.	
· Change in condition		
Melting point/Melting range:	-89.5 °C (-129.1 °F)	
Boiling point/Boiling range:	82 °C (179.6 °F)	
· Flash point:	13 °C (55.4 °F)	

Printing date 07/17/2024

Reviewed on 07/17/2024

Trade name:	Potassium	Hydroxide 0.5N
	in IPA, NI	ST Traceable

	(Contd. of page 5
Flammability (solid, gaseous):	Highly flammable.
Auto igniting:	425 °C (797 °F)
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
Explosion limits:	
Lower:	2 Vol %
Upper:	12 Vol %
Vapor pressure at 20 °C (68 °F):	43 hPa (32.3 mm Hg)
Density at 20 °C (68 °F):	0.80229 g/cm ³ (6.69511 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Fully miscible.
Partition coefficient (n-octanol/wate	r): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	96.5 %
VOC content:	96.50 %
	774.2 g/l / 6.46 lb/gal
Solids content:	3.5 %
Other information	No further relevant information available.

10 Stability and reactivity

• *Reactivity* No further relevant information available.

· Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

· Possibility of hazardous reactions No dangerous reactions known.

· Conditions to avoid No further relevant information available.

- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 7)

US

Printing date 07/17/2024

Reviewed on 07/17/2024

Trade name: Potassium Hydroxide 0.5N in IPA, NIST Traceable

(Contd. of page 6)

11 Toxicological information · Information on toxicological effects · Acute toxicity: · LD/LC50 values that are relevant for classification: ATE (Acute Toxicity Estimate) Oral LD50 14,276 mg/kg · Primary irritant effect: • on the skin: Caustic effect on skin and mucous membranes. • on the eye: Strong caustic effect. Strong irritant with the danger of severe eye injury. · Sensitization: No sensitizing effects known. · Additional toxicological information: The product shows the following dangers according to internally approved calculation methods for preparations: Corrosive Irritant Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach. · Carcinogenic categories · IARC (International Agency for Research on Cancer) CAS: 67-63-0 Isopropanol 3 · NTP (National Toxicology Program) None of the ingredients is listed. · OSHA-Ca (Occupational Safety & Health Administration) None of the ingredients is listed.

12 Ecological information

· Toxicity

- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

(Contd. on page 8)

Printing date 07/17/2024

Reviewed on 07/17/2024

Trade name: Potassium Hydroxide 0.5N in IPA, NIST Traceable

(Contd. of page 7)

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

· UN-Number · DOT, IMDG, IATA	UN2924
· UN proper shipping name · DOT	Flammable liquids, corrosive, n.o.s. (Isopropanol , Potassium Hydroxide)
· IMDG, IATA	, Folassium Hydroxide) FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Isopropanol , Potassium Hydroxide)
• Transport hazard class(es)	
·DOT	
RAMARIE LODO 3 B	
· Class · Label	3 Flammable liquids 3, 8
· IMDG	5, 0
· Class	3 Flammable liquids
· Label	3/8
· IATA	
· Class	3 Flammable liquids
· Label	3 (8)
· Packing group · DOT, IMDG, IATA	II
· Environmental hazards:	No
• Marine pollutant:	140

Printing date 07/17/2024

Reviewed on 07/17/2024

Trade name: Potassium Hydroxide 0.5N in IPA, NIST Traceable

	(Contd. of page
Hazard identification number (Kemler c	ode): 338
EMS Number:	F- E , S - C
Segregation groups	(SGG18) Alkalis
Stowage Category	В
Stowage Code	SW2 Clear of living quarters.
Transport in bulk according to Annex II	l of
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 1 L
	On cargo aircraft only: 5 L
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 2924 FLAMMABLE LIQUID, CORROSIVE, N.O.,
-	(ISOPROPANOL
	, POTASSIUM HYDROXIDE), 3 (8), II

15 Regulatory information

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

· Sara

• Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

CAS: 67-63-0 Isopropanol

· TSCA (Toxic Substances Control Act):

Isopropanol

Potassium Hydroxide

· Hazardous Air Pollutants

None of the ingredients is listed.

· Proposition 65

• Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

(Contd. on page 10)

ACTIVE

ACTIVE

US

Printing date 07/17/2024

· Carcinogenic categories

Reviewed on 07/17/2024

Trade name:	Potassium Hydroxide 0.5N
	in IPA, NIST Traceable

(Contd. of page 9)

EPA (Environmental Protection Agency)	
None of the ingredients is listed.	
TLV (Threshold Limit Value)	
CAS: 67-63-0 Isopropanol	A4
NIOSH-Ca (National Institute for Occupational Safety and Health)	· · ·
None of the ingredients is listed.	
GHS label elements The product is classified and labeled according to the Globally Harma Hazard pictograms	onized System (GHS).
GHS02 GHS05 GHS07	
Signal word Danger	
Hazard-determining components of labeling:	
Isopropanol	
Potassium Hydroxide	
Hazard statements	
Highly flammable liquid and vapor.	
Causes severe skin burns and eye damage.	
May cause drowsiness or dizziness.	
Precautionary statements	
Keep away from heat/sparks/open flames/hot surfaces No smoking.	
Ground/bond container and receiving equipment.	
Use explosion-proof electrical/ventilating/lighting/equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Do not breathe dusts or mists.	
Wash thoroughly after handling.	
Use only outdoors or in a well-ventilated area.	
Wear protective gloves/protective clothing/eye protection/face protection.	
If swallowed: Rinse mouth. Do NOT induce vomiting.	
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/s	shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if p	present and easy to a
Continue rinsing.	
Immediately call a poison center/doctor.	
Specific treatment (see on this label).	
Wash contaminated clothing before reuse.	
In case of fire: Use CO2, powder or water spray to extinguish.	
Store in a well-ventilated place. Keep container tightly closed.	
Store in a well-ventilated place. Keep cool.	
Store locked up.	
Dispose of contents/container in accordance with local/regional/national/international reg	ulations.
Chemical safety assessment: A Chemical Safety Assessment has not been carried out.	

(Contd. on page 11)

Printing date 07/17/2024

Reviewed on 07/17/2024

Trade name: Potassium Hydroxide 0.5N in IPA, NIST Traceable

(Contd. of page 10)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

· Contact:

Date of Preparation / Last Revision: · Date of preparation / last revision Revision 1.2 07/17/2024: Reviewed SDS for accuracy. MH/STN 07/17/2024 / 1.0 • Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit **REL:** Recommended Exposure Limit BEI: Biological Exposure Limit Flammable Liquids 2: Flammable liquids – Category 2 Skin Corrosion 1B: Skin corrosion/irritation - Category 1B Eye Damage 1: Serious eye damage/eye irritation - Category 1 Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) - Category 3 \cdot * Data compared to the previous version altered.