Printing date 05/15/2024

Reviewed on 05/15/2024

1 7 1	, · · · ·	
	entification	
	,	

- · Product identifier
- Trade name: Cyclohexanone 3,600 ppm Stock NSF Solvent 50:50 Chloroform/IPA
- · Article number: ND539
- Details of the supplier of the safety data sheet
 Manufacturer/Supplier: Aqua Solutions, Inc.
 6913 Highway 225 DEER PARK, TX 77536

USA 800-256-2586

- Information department: Technical Coordinator Sherman Nelson shermann@aquasolutions.org
 Emergency telephone number: Chemtrec: 800-424-9300
- Canutec: 613-996-6666

5 Highly flammable liquid and vapor.
5 Highly flammable liquid and vapor
· · · · · · · · · · · · · · · · · · ·
1 Toxic if inhaled.
1 Suspected of causing cancer.
1 Suspected of damaging fertility or the unborn child.
2 Causes damage to the central nervous system, the kidneys, the liver and the respiratory system through prolonged or repeated exposure.
2 Harmful if swallowed.
5 Causes skin irritation.
9 Causes serious eye irritation.
6 May cause drowsiness or dizziness.



Printing date 05/15/2024

Reviewed on 05/15/2024

Trade name: Cyclohexanone 3,600 ppm Stock NSF Solvent 50:50 Chloroform/IPA

(Contd. of page 1) · Hazard pictograms GHS02 GHS06 GHS07 GHS08 · Signal word Danger · Hazard-determining components of labeling: Chloroform Isopropanol · Hazard statements Highly flammable liquid and vapor. Harmful if swallowed. Toxic if inhaled. Causes skin irritation. Causes serious eye irritation. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. Causes damage to the central nervous system, the kidneys, the liver and the respiratory system through prolonged or repeated exposure. · Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Call a poison center/doctor if you feel unwell. Rinse mouth. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. Specific treatment (see on this label). Get medical advice/attention if you feel unwell. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. (Contd. on page 3)


us

Printing date 05/15/2024

Reviewed on 05/15/2024

Trade name:	Cyclohexanone 3,600 ppm Stock
	NSF Solvent 50:50 Chloroform/IPA

(Contd. of page 2)





· Other hazards

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

• Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 67-66-3	Chloroform	65.107%
CAS: 67-63-0	Isopropanol	34.533%
CAS: 108-94-1	Cyclohexanone 99.8%	0.36%

4 First-aid measures

· Description of first aid measures

• General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Remove breathing apparatus only after contaminated clothing have been completely removed.

In case of irregular breathing or respiratory arrest provide artificial respiration.

• After inhalation:

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Immediately call a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

(Contd. on page 4)

Printing date 05/15/2024

Reviewed on 05/15/2024

Trade name: Cyclohexanone 3,600 ppm Stock NSF Solvent 50:50 Chloroform/IPA

(Contd. of page 3)

5 *Fire-fighting measures*

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Mount respiratory protective device. Wear protective equipment. Keep unprotected persons away.
- $\cdot \textit{Environmental precautions: } Do not allow to enter sewers/ surface or ground water.$
- *Methods and material for containment and cleaning up:* Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.
- Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.
- · Protective Action Criteria for Chemicals

• PAC-1:		
CAS: 67-66-3	Chloroform	2 ppm
CAS: 67-63-0	Isopropanol	400 ppm
CAS: 108-94-1	Cyclohexanone 99.8%	60 ppm
· PAC-2:		
CAS: 67-66-3	Chloroform	64 ppm
CAS: 67-63-0	Isopropanol	2000* ppm
CAS: 108-94-1	Cyclohexanone 99.8%	830 ppm
· PAC-3:		
CAS: 67-66-3	Chloroform	3,200 ppm
CAS: 67-63-0	Isopropanol	12000** ppm
CAS: 108-94-1	Cyclohexanone 99.8%	5000* ppm

7 Handling and storage

- · Handling:
- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.

Printing date 05/15/2024

Reviewed on 05/15/2024

Trade name: Cyclohexanone 3,600 ppm Stock NSF Solvent 50:50 Chloroform/IPA

(Contd. of page 4)

Protect against electrostatic charges. Keep respiratory protective device available.

· Conditions for safe storage, including any incompatibilities

· Storage:

- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

• Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see section 7.

Com	ponents with limit values that require monitoring at the workplace:	
CAS:	: 67-66-3 Chloroform	
PEL	Ceiling limit value: 240 mg/m ³ , 50 ppm	
REL	Short-term value: 9.78* mg/m³, 2* ppm *60-min; See Pocket Guide App. A	
	Long-term value: 10 ppm A3	
CAS:	- 67-63-0 Isopropanol	
PEL	Long-term value: 980 mg/m ³ , 400 ppm	
REL	Short-term value: 1225 mg/m³, 500 ppm Long-term value: 980 mg/m³, 400 ppm	
	Short-term value: 400 ppm Long-term value: 200 ppm BEI, A4	
CAS:	: 108-94-1 Cyclohexanone 99.8%	
PEL	Long-term value: 200 mg/m ³ , 50 ppm	
	Long-term value: 100 mg/m³, 25 ppm Skin	
TLV	Short-term value: 50 ppm Long-term value: 20 ppm Skin, BEI, A3	
Ingre	edients with biological limit values:	
CAS:	: 67-63-0 Isopropanol	
BEI	40 mg/L LD50 Intraperitoneal: urine Time: end of shift at end of workweek LD50: Acetone (background, nonspecific)	
		(Contd. on pag

Printing date 05/15/2024

Reviewed on 05/15/2024

Trade name: Cyclohexanone 3,600 ppm Stock NSF Solvent 50:50 Chloroform/IPA

(Contd. of page 5)

CAS: 108-94-1 Cyclohexanone 99.8%

BEI 80 mg/L

LD50 Intraperitoneal: urine Time: end of shift at end of workweek LD50: 1.2-Cyclohexanediol (with hydrolysis, nonspecific, nonquantitative)

8 mg/L LD50 Intraperitoneal: urine Time: end of shift LD50: Cyclohexanol (with hydrolysis, nonspecific, nonquantitative)

· Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. • Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation • Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

(Contd. on page 7)

Printing date 05/15/2024

Reviewed on 05/15/2024

Trade name: Cyclohexanone 3,600 ppm Stock NSF Solvent 50:50 Chloroform/IPA

(Contd. of page 6)

9 Physical and chemical propert	
\cdot Information on basic physical and ch	hemical properties
· General Information	
· Appearance:	7 · · · 1
Form: Color:	Liquid Colorless
· Odor:	Alcohol-like
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	61.5 °C (142.7 °F)
· Flash point:	13 °C (55.4 °F)
· Flammability (solid, gaseous):	Highly flammable.
· Auto igniting:	425 °C (797 °F)
· Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
• Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
· Explosion limits:	
Lower:	2 Vol %
Upper:	12 Vol %
· Vapor pressure at 20 °C (68 °F):	210 hPa (157.5 mm Hg)
· Density at 20 °C (68 °F):	1 g/cm ³ (8.345 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water	r): Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	34.9 %
VOC content:	34.89 %
	348.9 g/l / 2.91 lb/gal
Solids content:	0.0 %
• Other information	No further relevant information available.

(Contd. on page 8)

Printing date 05/15/2024

Reviewed on 05/15/2024

Trade name: Cyclohexanone 3,600 ppm Stock NSF Solvent 50:50 Chloroform/IPA

(Contd. of page 7)

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Oral	LD50	768 mg/kg
Dermal	LD50	83,333 mg/kg
Inhalative	LC50/4h	4.61 mg/l

· Primary irritant effect:

• on the skin: Irritant to skin and mucous membranes.

• on the eye: Irritating effect.

- Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Toxic

Harmful

Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)		
CAS: 67-66-3	Chloroform	2B
CAS: 67-63-0	Isopropanol	3
CAS: 108-94-1	Cyclohexanone 99.8%	3
· NTP (National Toxicology Program)		
CAS: 67-66-3 Chloroform R		
· OSHA-Ca (Occupational Safety & Health Administration)		
None of the ingredients is listed.		

12 Ecological information

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.

(Contd. on page 9)

US

Printing date 05/15/2024

Reviewed on 05/15/2024

Trade name: Cyclohexanone 3,600 ppm Stock NSF Solvent 50:50 Chloroform/IPA

(Contd. of page 8)

\cdot Additional ecological information:

· General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground.

· Results of PBT and vPvB assessment

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

 $\cdot \textit{Other adverse effects}$ No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:

· Recommendation: Disposal must be made according to official regulations.

· UN-Number	
· DOT, IMDG, IATA	UN1992
\cdot UN proper shipping name	
·DOT	Flammable liquids, toxic, n.o.s. (Isopropanol
	, Chloroform)
· IMDG, IATA	FLAMMABLE LIQUID, TOXIC, N.O.S. (Isopropanol , Chloroform)
· Transport hazard class(es)	
·DOT	
· Class	3 Flammable liquids
· Label	3, 6.1
· IMDG	
· Class	3 Flammable liquids
· Label	3/6.1

Printing date 05/15/2024

Reviewed on 05/15/2024

Trade name:	: Cyclohexanone 3,600 ppm Stock		
	NSF Solvent 50:50 Chloroform/IPA		

	(Contd. of page
IATA	
Class	3 Flammable liquids
Label	3 (6.1)
Packing group	
DOT, IMDG, IATA	II
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Flammable liquids
Hazard identification number (Kemler code):	
EMS Number:	F-E,S-D
Stowage Category	B CH
Stowage Code	SW2 Clear of living quarters.
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L
	On cargo aircraft only: 60 L
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1992 FLAMMABLE LIQUID, TOXIC, N.O.S
	(ISOPROPANOL
	, CHLOROFORM), 3 (6.1), II

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara

· Section 355 (extremely hazardous substances):	
CAS: 67-66-3 Chloroform	
· Section 313 (Specific toxic chemical listings):	
CAS: 67-66-3 Chloroform	
CAS: 67-63-0 Isopropanol	
· TSCA (Toxic Substances Control Act):	
Chloroform	ACTIVE
Isopropanol	ACTIVE
Cyclohexanone 99.8%	ACTIVE
	(Contd. on page 11)

Printing date 05/15/2024

Reviewed on 05/15/2024

Trade name: Cyclohexanone 3,600 ppm Stock NSF Solvent 50:50 Chloroform/IPA

(Contd. of page 10)

B2, L, NL

A3

A4

AЗ

Hazardous Air Pollutants
 CAS: 67-66-3 Chloroform

· Proposition 65

· Chemicals known to cause cancer:

CAS: 67-66-3 Chloroform

 \cdot Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

• Chemicals known to cause developmental toxicity:

CAS: 67-66-3 Chloroform

· Carcinogenic categories

· EPA (Environmental Protection Agency)

CAS: 67-66-3 Chloroform

· TLV (Threshold Limit Value)

CAS: 67-66-3 Chloroform

CAS: 67-63-0 Isopropanol

CAS: 108-94-1 Cyclohexanone 99.8%

· NIOSH-Ca (National Institute for Occupational Safety and Health)

CAS: 67-66-3 Chloroform

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

• Hazard-determining components of labeling: Chloroform Isopropanol • Hazard statements

Highly flammable liquid and vapor.

Harmful if swallowed. Toxic if inhaled.

Causes skin irritation.

Causes serious eye irritation.

Suspected of causing cancer.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

Causes damage to the central nervous system, the kidneys, the liver and the respiratory system through prolonged or repeated exposure.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

(Contd. on page 12)

Printing date 05/15/2024

Reviewed on 05/15/2024

Trade name: Cyclohexanone 3,600 ppm Stock NSF Solvent 50:50 Chloroform/IPA

(Contd. of page 11) Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Call a poison center/doctor if you feel unwell. Rinse mouth. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. Specific treatment (see on this label). Get medical advice/attention if you feel unwell. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department. · Contact: Date of Preparation / Last Revision: · Date of preparation / last revision Revision 1.2, 05/15/2024: Reviewed SDS for accuracy. MH/STN Revision 0.0, 06-13-2023: Creation date for SDS. STN 05/15/2024 · Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health

(Contd. on page 13)

Printing date 05/15/2024

Reviewed on 05/15/2024

Trade name: Cyclohexanone 3,600 ppm Stock NSF Solvent 50:50 Chloroform/IPA

(Contd. of page 12)

TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flammable Liquids 2: Flammable liquids – Category 2 Acute Toxicity - Oral 4: Acute toxicity – Category 4 Acute Toxicity - Inhalation 3: Acute toxicity – Category 3 Skin Irritation 2: Skin corrosion/irritation – Category 2 Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A Carcinogenicity 2: Carcinogenicity – Category 2 Toxic to Reproduction 2: Reproductive toxicity – Category 2 Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3 Specific Target Organ Toxicity - Repeated Exposure 1: Specific target organ toxicity (repeated exposure) – Category 1 • * Data compared to the previous version altered.