Printing date 04/20/2018 Reviewed on 04/20/2018

1 Identification

· Product identifier

· Trade name: Acetone, Laboratory Grade

· Article number: 37009-00

• CAS Number: 67-64-1 • EC number: 200-662-2

• Index number: 606-001-00-8

- · Application of the substance / the mixture Laboratory chemicals
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586

· Information department:

techservices@ofite.com Technical Coordinator

Sherman Nelson sherman@aquasolutions.org

· Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666



2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS07

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements The substance is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS02

GHS07

- · Signal word Danger
- · Hazard statements

Highly flammable liquid and vapor.

Causes serious eye irritation.

(Contd. on page 2)

Printing date 04/20/2018 Reviewed on 04/20/2018

Trade name: Acetone, Laboratory Grade

(Contd. of page 1)

May cause drowsiness or dizziness.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Call a poison center/doctor if you feel unwell.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2 Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 2 Fire = 3Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Substances
- · CAS No. Description 67-64-1 Acetone
- · Identification number(s)
- · EC number: 200-662-2
- · Index number: 606-001-00-8

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.

(Contd. on page 3)

Printing date 04/20/2018 Reviewed on 04/20/2018

Trade name: Acetone, Laboratory Grade

(Contd. of page 2)

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

- · Protective Action Criteria for Chemicals
- · **PAC-1**: 200 ppm
- · PAC-2: 3200* ppm
- · PAC-3: 5700* ppm

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.

(Contd. on page 4)

Printing date 04/20/2018 Reviewed on 04/20/2018

Trade name: Acetone, Laboratory Grade

(Contd. of page 3)

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

CAS: 67-64-1 Acetone

PEL Long-term value: 2400 mg/m³, 1000 ppm REL Long-term value: 590 mg/m³, 250 ppm TLV Short-term value: 1187 mg/m³, 500 ppm Long-term value: 594 mg/m³, 250 ppm

BEI

· Ingredients with biological limit values:

CAS: 67-64-1 Acetone

BEI 50 mg/L

LD50 Intraperitoneal: urine

Time: end of shift

LD50: Acetone (nonspecific)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

Printing date 04/20/2018 Reviewed on 04/20/2018

Trade name: Acetone, Laboratory Grade

· Eye protection:

(Contd. of page 4)



Tightly sealed goggles

· Body protection: Protective work clothing

9 Physical and chemical properties		
· Information on basic physical and c · General Information	hemical properties	
· Appearance:	Liquid	
Form: Color:	Liquid Colorless	
· Odor:	Coloriess Mild	
· Oaor: · Odor threshold:	мна Not determined.	
· pH-value:	Not determined.	
•	Trot determined.	
· Change in condition	047°C (1295°E)	
Melting point/Melting range:	-94.7 °C (-138.5 °F) 55.8-56.6 °C (132.4-133.9 °F)	
Boiling point/Boiling range:		
· Flash point:	<-18 °C (<-0.4 °F)	
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:	465 °C (869 °F)	
Decomposition temperature:	Not determined.	
· Auto igniting:	Not determined.	
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vape mixtures are possible.	
· Explosion limits:		
Lower:	2.6 Vol %	
Upper:	13 Vol %	
· Vapor pressure at 20 °C (68 °F):	233 hPa (174.8 mm Hg)	
· Density at 20 °C (68 °F):	0.79 g/cm³ (6.59255 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Fully miscible.	
· Partition coefficient (n-octanol/wate	•	
,	.,	
· Viscosity: Dynamic at 20 °C (68 °F):	32 mPas	
Ninematic:	Not determined.	
• Other information	Noi determined. No further relevant information available.	

Printing date 04/20/2018 Reviewed on 04/20/2018

Trade name: Acetone, Laboratory Grade

(Contd. of page 5)

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:
- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer) Substance is not listed.
- · NTP (National Toxicology Program) Substance is not listed.
- · OSHA-Ca (Occupational Safety & Health Administration) Substance is not listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Assessment by list): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

(Contd. on page 7)

Printing date 04/20/2018 Reviewed on 04/20/2018

Trade name: Acetone, Laboratory Grade

 $\cdot \textbf{Recommended cleansing agent:} \ Water, if necessary with cleansing agents.$

(Contd. of page 6)

UN-Number DOT, IMDG, IATA UN proper shipping name DOT Acetone IMDG, IATA ACETONE Transport hazard class(es) DOT Class Label 3 Flammable liquids 4 Flammable liquids 5 Flammable liquids 6 Flammable liquids 7 Flammable liquids 8 Flammable liquids 8 Flammable liquids 8 Flammable liquids 9 Flammable liquids 1 Flammable liqui	
UN proper shipping name DOT Acetone IMDG, IATA ACETONE Transport hazard class(es) DOT Class 3 Flammable liquids 3 IMDG, IATA Class 3 Flammable liquids 3 IMDG, IATA Class 3 Flammable liquids 4 Flammable liquids 5 Flammable liquids 6 Flammable liquids 7 Flammable liquids 8 Flammable liquids 8 Flammable liquids 9 Flammable liquids 1 Flammable	
Acetone IMDG, IATA ACETONE Transport hazard class(es) DOT Class Label Class Label 3 IMDG, IATA Class Label A Flammable liquids 3 IMDG, IATA Class Label A Flammable liquids B Hammable liquids	
IMDG, IATA Transport hazard class(es) DOT Class Label 3 IMDG, IATA Class 3 Flammable liquids 3 IMDG, IATA Class 3 Flammable liquids 3 IMDG, IATA II Environmental hazards: Marine pollutant: No Special precautions for user Danger code (Kemler): 33 EMS Number: F-E,S-D Stowage Category Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Transport/Additional information: DOT Quantity limitations On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L Hazardous substance: IMDG	
Class 3 Flammable liquids Label 3 IMDG, IATA Class 3 Flammable liquids Label 3 Packing group DOT, IMDG, IATA II Environmental hazards: Marine pollutant: No Special precautions for user Danger code (Kemler): 33 EMS Number: F-E,S-D Stowage Category E Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Transport/Additional information: DOT Quantity limitations On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L Hazardous substance: 5000 lbs, 2270 kg	
Class 3 Flammable liquids 3 IMDG, IATA Class 3 Flammable liquids Label 3 Class 3 Flammable liquids Label 3 Packing group DOT, IMDG, IATA II Environmental hazards: Marine pollutant: No Special precautions for user Danger code (Kemler): 33 EMS Number: F-E,S-D Stowage Category E Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. Transport/Additional information: DOT Quantity limitations On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L Hazardous substance: 5000 lbs, 2270 kg	
Class 3 Flammable liquids 3 IMDG, IATA Class 3 Flammable liquids Label 3 Class 3 Flammable liquids Label 3 Packing group DOT, IMDG, IATA II Environmental hazards: Marine pollutant: No Special precautions for user Danger code (Kemler): 33 EMS Number: F-E,S-D Stowage Category E Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. Transport/Additional information: DOT Quantity limitations On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L Hazardous substance: 5000 lbs, 2270 kg	
Label 3 IMDG, IATA Class 3 Flammable liquids 3 Packing group DOT, IMDG, IATA II Environmental hazards: Marine pollutant: No Special precautions for user Warning: Flammable liquids Danger code (Kemler): 33 EMS Number: F-E,S-D Stowage Category E Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. Transport/Additional information: DOT Quantity limitations On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L Hazardous substance: 5000 lbs, 2270 kg	
Class 3 Flammable liquids Label 3 Packing group DOT, IMDG, IATA II Environmental hazards: Marine pollutant: No Special precautions for user Warning: Flammable liquids Danger code (Kemler): 33 EMS Number: F-E,S-D Stowage Category E Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. Transport/Additional information: DOT Quantity limitations On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L Hazardous substance: 5000 lbs, 2270 kg	
Class 3 Flammable liquids Label 3 Packing group DOT, IMDG, IATA II Environmental hazards: Marine pollutant: No Special precautions for user Warning: Flammable liquids Danger code (Kemler): 33 EMS Number: F-E,S-D Stowage Category E Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. Transport/Additional information: DOT Quantity limitations On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L Hazardous substance: 5000 lbs, 2270 kg	
Label 3 Packing group DOT, IMDG, IATA II Environmental hazards: Marine pollutant: No Special precautions for user Warning: Flammable liquids Danger code (Kemler): 33 EMS Number: F-E,S-D Stowage Category E Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. Transport/Additional information: DOT Quantity limitations On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L Hazardous substance: 5000 lbs, 2270 kg	
DOT, IMDG, IATA Environmental hazards: Marine pollutant: No Special precautions for user Danger code (Kemler): EMS Number: F-E,S-D Stowage Category E Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. Transport/Additional information: DOT Quantity limitations On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L Hazardous substance: 5000 lbs, 2270 kg	
Marine pollutant: No Special precautions for user Danger code (Kemler): BMS Number: Stowage Category Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. Transport/Additional information: DOT Quantity limitations On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L Hazardous substance: IMDG	
Danger code (Kemler): EMS Number: F-E,S-D Stowage Category E Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. Transport/Additional information: DOT Quantity limitations On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L Hazardous substance: 5000 lbs, 2270 kg	
Danger code (Kemler): EMS Number: F-E,S-D Stowage Category E Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. Transport/Additional information: DOT Quantity limitations On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L Hazardous substance: 5000 lbs, 2270 kg	
Stowage Category Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. Transport/Additional information: DOT Quantity limitations On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L Hazardous substance: 5000 lbs, 2270 kg	
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. Transport/Additional information: DOT Quantity limitations On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L Hazardous substance: 5000 lbs, 2270 kg	
MARPOL73/78 and the IBC Code Not applicable. Transport/Additional information: DOT Quantity limitations On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L Hazardous substance: IMDG	
Transport/Additional information: DOT Quantity limitations On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L Hazardous substance: 5000 lbs, 2270 kg	
Quantity limitations On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L Hazardous substance: 5000 lbs, 2270 kg	
Quantity limitations On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L Hazardous substance: 5000 lbs, 2270 kg IMDG	
On cargo aircraft only: 60 L Hazardous substance: 5000 lbs, 2270 kg IMDG	
IMDG	
Limited quantities (LQ) 1L	
· · · · · · · · · · · · · · · · · · ·	
Excepted quantities (EQ) Code: E2	
Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml	

Printing date 04/20/2018 Reviewed on 04/20/2018

Trade name: Acetone, Laboratory Grade

(Contd. of page 7)

· UN ''Model Regulation'': UN 1090 ACETONE, 3, II

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances): Substance is not listed.
- · Section 313 (Specific toxic chemical listings): Substance is not listed.
- · TSCA (Toxic Substances Control Act):

Acetone

- · Proposition 65
- · Chemicals known to cause cancer: Substance is not listed.
- · Chemicals known to cause reproductive toxicity for females: Substance is not listed.
- · Chemicals known to cause reproductive toxicity for males: Substance is not listed.
- · Chemicals known to cause developmental toxicity: Substance is not listed.
- · Carcinogenic categories
- · EPA (Environmental Protection Agency) I
- · TLV (Threshold Limit Value established by ACGIH) A4
- · NIOSH-Ca (National Institute for Occupational Safety and Health) Substance is not listed.
- · GHS label elements The substance is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS02

GHS07

- · Signal word Danger
- · Hazard statements

Highly flammable liquid and vapor.

Causes serious eye irritation.

May cause drowsiness or dizziness.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Call a poison center/doctor if you feel unwell.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

(Contd. on page 9)

Printing date 04/20/2018 Reviewed on 04/20/2018

Trade name: Acetone, Laboratory Grade

(Contd. of page 8)

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:
- · Date of preparation / last revision

Revision 1.0, 3/28/2018 Revised DOT to UN1993 from UN1294. DL 04/20/2018 / -

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A

 $STOT\,SE\,3:\,Specific\,target\,organ\,toxicity\,(single\,exposure)-Category\,3$

US