Printing date 07/25/2024


Reviewed on 07/25/2024

1 Identification

- · Product identifier
- Trade name: 200 grains/gal CO2 200 grains/gal H2S in 40% v/v MDEA
- · Article number: AM448
- Details of the supplier of the safety data sheet
 Manufacturer/Supplier: Aqua Solutions, Inc.
 6913 Highway 225 DEER PARK, TX 77536
- USA 800-256-2586
- Information department: Technical Coordinator Sherman Nelson shermann@aquasolutions.org Technical Coordinator Sherman Nelson shermann@aquasolutions.org
- Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666

2 Hazard(s) identification

· Classification of the substance or mixture



Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.



Acute Toxicity - Oral 4 Eye Irritation 2A H302 Harmful if swallowed. H319 Causes serious eye irritation.

· Label elements

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



Signal word Warning
Hazard statements
Harmful if swallowed.
Causes serious eye irritation.
May cause damage to organs through prolonged or repeated exposure.
Precautionary statements
Do not breathe dust/fume/gas/mist/vapors/spray.
Wash thoroughly after handling.

(Contd. on page 2)



⁻ US

Printing date 07/25/2024

Reviewed on 07/25/2024

Trade name: 200 grains/gal CO2 200 grains/gal H2S in 40% v/v MDEA

(0	Contd. of page 1)
Do not eat, drink or smoke when using this product.	
Wear eye protection / face protection.	
If swallowed: Call a poison center/doctor if you feel unwell.	
Rinse mouth.	
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and	d easy to do.
Continue rinsing.	
Get medical advice/attention if you feel unwell.	
If eye irritation persists: Get medical advice/attention.	
Dispose of contents/container in accordance with local/regional/national/international regulations.	
· Classification system:	
· NFPA ratings (scale 0 - 4)	
Health = 2	
Fire = 1	
2 0 Reactivity = 0	
· HMIS-ratings (scale 0 - 4)	
HEALTH 2 $Health = 2$	
FIRE 1 Fire = 1	
$\frac{1}{\text{REACTIVITY}[0]} Reactivity = 0$	
REACTIVITY 0 Reactivity = 0	
· Other hazards	
· Results of PBT and vPvB assessment	
· PBT: Not applicable.	
• vPvB: Not applicable.	
3 Composition/information on ingredients	
· Chemical characterization: Mixtures	
• Description: Mixture of the substances listed below with nonhazardous additions.	
· Dangerous components:	
CAS: 105-59-9 N-Methyldiethanolamine, 99%	40.0%
CAS: 7783-06-4 Hydrogen Sulfide	0.343%
· Table of Nonhazardous Ingredients	
CAS: 7732-18-5 Water	59.314%
CAS: 124-38-9 Carbon Dioxide Gas	0.343%

4 First-aid measures

· Description of first aid measures

• General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.

• After eye contact:

- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: Immediately call a doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)

- US

(Contd. of page 2)

Safety Data Sheet acc. to OSHA HCS

Printing date 07/25/2024

Reviewed on 07/25/2024

Trade name: 200 grains/gal CO2

200 grains/gal H2S in 40% v/v MDEA

• *Indication of any immediate medical attention and special treatment needed No further relevant information available.*

5 *Fire-fighting measures*

- · Extinguishing media
- Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.
 Environmental precautions: Do not allow product to reach sewage system or any water course.
- Inform respective authorities in case of seepage into water course or sewage system.
- Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

- *Methods and material for containment and cleaning up:* Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.
- **Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.
- · Protective Action Criteria for Chemicals

· PAC-1:		
CAS: 124-38-9	Carbon Dioxide Gas	54000 mg/m3
CAS: 7783-06-4	Hydrogen Sulfide	0.51 ppm
· PAC-2:		
CAS: 124-38-9	Carbon Dioxide Gas	72000 mg/m3
CAS: 7783-06-4	Hydrogen Sulfide	27 ppm
· PAC-3:		
CAS: 124-38-9	Carbon Dioxide Gas	90000 mg/m3
CAS: 7783-06-4	Hydrogen Sulfide	50 ppm

7 Handling and storage

· Handling:

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires: Keep respiratory protective device available.

(Contd. on page 4)

Printing date 07/25/2024

Reviewed on 07/25/2024

Trade name: 200 grains/gal CO2 200 grains/gal H2S in 40% v/v MDEA

(Contd. of page 3)

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

CAS: 7783-06-4 Hydrogen Sulfide

- PEL Ceiling limit value: 20; 50* ppm
 - *10-min peak; once per 8-hr shift
- REL Ceiling limit value: 15* mg/m³, 10* ppm *10-min
- TLV Short-term value: 5 ppm Long-term value: 1 ppm

• Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes.

Avoid contact with the eyes and skin.

• Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

⁻ US

Printing date 07/25/2024

Reviewed on 07/25/2024

Trade name: 200 grains/gal CO2 200 grains/gal H2S in 40% v/v MDEA

(Contd. of page 4)

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

Information on basic physical and c	hemical properties	
General Information		
Appearance:		
Form:	Liquid	
Color:	Colorless	
Odor:	Like rotten eggs (mercaptans)	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	Undetermined.	
Flash point:	260 °C (500 °F)	
Flammability (solid, gaseous):	Not applicable.	
Auto igniting:	265 °C (509 °F)	
Decomposition temperature:	Not determined.	
Ignition temperature:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
Density:	Not determined.	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Fully miscible.	
Partition coefficient (n-octanol/wate	r): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	

Printing date 07/25/2024

Reviewed on 07/25/2024

Trade name:	200 grains/gal CO2
	200 grains/gal H2S in 40% v/v MDEA

		(Contd. of page 5
· Solvent content:		
Water:	59.3 %	
VOC content:	0.00 %	
	0.0 g/l / 0.00 lb/gal	
Solids content:	0.0 %	
• Other information	No further relevant information available.	

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

· Acute toxicity:

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Inhalative LC50/4h 29,155 mg/l

· Primary irritant effect:

• on the skin: No irritant effect.

- on the eye: Irritating effect.
- Sensitization: No sensitizing effects known.
- $\cdot \textit{Additional toxicological information:}$

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

• Aquatic toxicity: No further relevant information available.

· Persistence and degradability No further relevant information available.

(Contd. on page 7)

US

Printing date 07/25/2024

Reviewed on 07/25/2024

Trade name: 200 grains/gal CO2 200 grains/gal H2S in 40% v/v MDEA

(Contd. of page 6)

- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:
- Water hazard class 1 (Self-assessment): slightly hazardous for water
- Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- *Recommendation: Disposal must be made according to official regulations.*
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information · UN-Number · DOT, IMDG, IATA UN3287 · UN proper shipping name $\cdot DO\bar{T}$ Toxic liquid, inorganic, n.o.s. (Hydrogen Sulfide) · IMDG, IATA TOXIC LIQUID, INORGANIC, N.O.S. (Hydrogen Sulfide) · Transport hazard class(es) $\cdot DOT$ ŤOXIČ · Class 6.1 Toxic substances · Label 6.1 · IMDG, IATA · Class 6.1 Toxic substances · Label 6.1 · Packing group Π · DOT, IMDG, IATA (Contd. on page 8) US

Printing date 07/25/2024

Reviewed on 07/25/2024

Trade name: 200 grains/gal CO2 200 grains/gal H2S in 40% v/v MDEA

	(Contd. of page 7
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Warning: Toxic substances
Stowage Category	B
Stowage Code	SW2 Clear of living quarters.
Transport in bulk according to Annex	II of
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L
2	On cargo aircraft only: 60 L
IMDG	
Limited quantities (LQ)	100 ml
Excepted quantities $(\widetilde{E}Q)$	Code: E4
	Maximum net quantity per inner packaging: 1 ml
	Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 3287 TOXIC LIQUID, INORGANIC, N.O.S. (HYDROGE)
0	SULFIDE), 6.1, II

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

· Sara

· Section 355 (extremely hazardous substances):

CAS: 7783-06-4 Hydrogen Sulfide

 \cdot Section 313 (Specific toxic chemical listings):

CAS: 7783-06-4 Hydrogen Sulfide

· TSCA (Toxic Substances Control Act):

Water	ACTIVE
N-Methyldiethanolamine, 99%	ACTIVE
Carbon Dioxide Gas	ACTIVE
Hydrogen Sulfide	ACTIVE
· Hazardous Air Pollutants	

None of the ingredients is listed.

· Proposition 65

 \cdot Chemicals known to cause cancer:

None of the ingredients is listed.

 \cdot Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

(Contd. on page 9)

US

Printing date 07/25/2024

Reviewed on 07/25/2024

Trade name: 200 grains/gal CO2

200 grains/gal H2S in 40% v/v MDEA

(Contd. of page 8)

Ι

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

CAS: 7783-06-4 Hydrogen Sulfide

· TLV (Threshold Limit Value)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). · Hazard pictograms



· Signal word Warning

· Hazard statements

Harmful if swallowed. Causes serious eye irritation.

May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear eye protection / face protection.

If swallowed: Call a poison center/doctor if you feel unwell.

Rinse mouth.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Get medical advice/attention if you feel unwell.

If eye irritation persists: Get medical advice/attention.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

· Contact:

- Date of Preparation / Last Revision:
- · Date of preparation / last revision
- Revision 1.2 07/25/2024: Reviewed SDS for accuracy. MH/STN 07/25/2024 / 1.1
- · Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association

(Contd. on page 10)

Printing date 07/25/2024

Reviewed on 07/25/2024

Trade name: 200 grains/gal CO2 200 grains/gal H2S in 40% v/v MDEA

	(Contd. of page 9)	
EINECS: European Inventory of Existing Commercial Chemical Substances		
ELINCS: European List of Notified Chemical Substances		
CAS: Chemical Abstracts Service (division of the American Chemical Society)		
NFPA: National Fire Protection Association (USA)		
HMIS: Hazardous Materials Identification System (USA)		
VOC: Volatile Organic Compounds (USA, EU)		
LC50: Lethal concentration, 50 percent		
LD50: Lethal dose, 50 percent		
PBT: Persistent, Bioaccumulative and Toxic		
vPvB: very Persistent and very Bioaccumulative		
NIOSH: National Institute for Occupational Safety		
OSHA: Occupational Safety & Health		
TLV: Threshold Limit Value		
PEL: Permissible Exposure Limit		
REL: Recommended Exposure Limit		
Acute Toxicity - Oral 4: Acute toxicity – Category 4		
Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A		
Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2		
• * Data compared to the previous version altered.		
	US	