Printing date 07/25/2024 Reviewed on 07/25/2024

1 Identification

· Product identifier

· Trade name: 400 grains/gal CO₂ and H₂S in 40% v/v MDEA + 5% v/v MEA

· Article number: AM451

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586

· Information department:

Technical Coordinator

Sherman Nelson shermann@aquasolutions.org

· Emergency telephone number:

Chemtrec: 800-424-9300 Canutec: 613-996-6666



2 Hazard(s) identification

· Classification of the substance or mixture



GHS05 Corrosion

Eye Damage 1 H318 Causes serious eye damage.



GHS07

Skin Irritation 2 H315 Causes skin irritation.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



GHS05

- · Signal word Danger
- · Hazard-determining components of labeling:

2-Aminoethanol (Monoethanolamine), Reagent Grade

· Hazard statements

Causes skin irritation.

Causes serious eye damage.

· Precautionary statements

Wash thoroughly after handling.

Wear protective gloves / eye protection / face protection.

If on skin: Wash with plenty of water.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

(Contd. on page 2)

Printing date 07/25/2024 Reviewed on 07/25/2024

Trade name: 400 grains/gal CO₂ and H₂S in 40% v/v MDEA + 5% v/v MEA

(Contd. of page 1)

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3 Fire = 1Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 3 Fire = 1Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of the substances listed below with nonhazardous additions.

	· Dangerous comp	ponents:						
	CAS: 105-59-9 N-Methyldiethanolamine, 99%							
CAS: 141-43-5 2-Aminoethanol (Monoethanolamine), Reagent Grade 4.9								
	CAS: 7783-06-4 Hydrogen Sulfide 0.674							
	· Table of Nonhazardous Ingredients							
	CAS: 7732-18-5	Water	52.796%					
	CAS: 124-38-9	Carbon Dioxide Gas	0.674%					

4 First-aid measures

- · Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

HS

Printing date 07/25/2024 Reviewed on 07/25/2024

Trade name: 400 grains/gal CO₂ and H₂S in 40% v/v MDEA + 5% v/v MEA

(Contd. of page 2)

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to section 13.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:	v					
CAS: 141-43-5	2-Aminoethanol (Monoethanolamine), Reagent Grade	6 ppm				
CAS: 124-38-9	CAS: 124-38-9 Carbon Dioxide Gas					
CAS: 7783-06-4	CAS: 7783-06-4 Hydrogen Sulfide					
· PAC-2:						
CAS: 141-43-5	2-Aminoethanol (Monoethanolamine), Reagent Grade	170 ppm				
CAS: 124-38-9	Carbon Dioxide Gas	72000 mg/m3				
CAS: 7783-06-4	Hydrogen Sulfide	27 ppm				
· PAC-3:						
CAS: 141-43-5	2-Aminoethanol (Monoethanolamine), Reagent Grade	1,000 ppm				
CAS: 124-38-9	Carbon Dioxide Gas	90000 mg/m3				
CAS: 7783-06-4	Hydrogen Sulfide	50 ppm				

7 Handling and storage

- · Handling:
- · Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.

(Contd. on page 4)

Printing date 07/25/2024 Reviewed on 07/25/2024

Trade name: 400 grains/gal CO₂ and H₂S in 40% v/v MDEA + 5% v/v MEA

(Contd. of page 3)

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- \cdot *Specific end use(s) No further relevant information available.*

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

CAS:	141-43-5	2-Amin	ioetl	ianoi	l (Monoethanolamine), Reagent Grade
	_		-		2

PEL Long-term value: 6 mg/m³, 3 ppm REL Short-term value: 15 mg/m³, 6 ppm

Long-term value: 8 mg/m³, 3 ppm

TLV Short-term value: 6 ppm Long-term value: 3 ppm

CAS: 7783-06-4 Hydrogen Sulfide

PEL Ceiling limit value: 20; 50* ppm *10-min peak; once per 8-hr shift

REL Ceiling limit value: 15* mg/m³, 10* ppm

*10-min

TLV Short-term value: 5 ppm Long-term value: 1 ppm

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

- · Breathing equipment: Not required.
- · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

Printing date 07/25/2024 Reviewed on 07/25/2024

Trade name: 400 grains/gal CO₂ and H₂S in 40% v/v MDEA + 5% v/v MEA

(Contd. of page 4)

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



· Viscosity: Dynamic:

Kinematic:

Tightly sealed goggles

· Body protection: Protective work clothing

Information on basic physical and o	chemical properties	
General Information		
Appearance:		
Form:	Liquid	
Color:	Green	
Odor:	Pungent	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	100 °C (212 °F)	
Flash point:	127 °C (260.6 °F)	
Flammability (solid, gaseous):	Not applicable.	
Auto igniting:	265 °C (509 °F)	
Decomposition temperature:	Not determined.	
Ignition temperature:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
Density at 20 °C (68 °F):	1.00266 g/cm³ (8.3672 lbs/gal)	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water: Fully miscible.		

Not determined.

Not determined.

(Contd. on page 6)

Printing date 07/25/2024 Reviewed on 07/25/2024

Trade name: 400 grains/gal CO2 and H2S in 40% v/v MDEA + 5% v/v MEA

		(Contd. of page 5
· Solvent content:		
Organic solvents:	5.0 %	
Water:	52.8 %	
VOC content:	4.98 %	
	49.9 g/l / 0.42 lb/gal	
Solids content:	0.0 %	
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Oral	LD50	41,154 mg/kg (rat)
Dermal	LD50	20,075 mg/kg (rabbit)
Inhalative	LC50/4h	218 mg/l

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- on the eye: Strong irritant with the danger of severe eye injury.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

US

Printing date 07/25/2024 Reviewed on 07/25/2024

Trade name: 400 grains/gal CO₂ and H₂S in 40% v/v MDEA + 5% v/v MEA

(Contd. of page 6)

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

UN-Number DOT, ADN, IMDG, IATA	Not regulated	
	noi reguiaca	
UN proper shipping name DOT, ADN, IMDG, IATA	Not regulated	
Transport hazard class(es)		
DOT, ADN, IMDG, IATA Class	Not regulated	
Packing group DOT, IMDG, IATA	Not regulated	
Environmental hazards:	Not applicable.	
Special precautions for user	Not applicable.	
Transport in bulk according to Annex I. MARPOL73/78 and the IBC Code	I of Not applicable.	
UN "Model Regulation":	Not regulated	

Printing date 07/25/2024 Reviewed on 07/25/2024

Trade name: 400 grains/gal CO2 and H2S in 40% v/v MDEA + 5% v/v MEA

(Contd. of page 7)

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara

· Section 355	(extremely	hazardous	substances):

CAS: 7783-06-4 Hydrogen Sulfide

· Section 313 (Specific toxic chemical listings):

CAS: 7783-06-4 Hydrogen Sulfide

· TSCA (Toxic Substances Control Act):

Water	ACTIVE
N-Methyldiethanolamine, 99%	ACTIVE
2-Aminoethanol (Monoethanolamine), Reagent Grade	ACTIVE
Carbon Dioxide Gas	ACTIVE
Hydrogen Sulfide	ACTIVE

· Hazardous Air Pollutants

None of the ingredients is listed.

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

 $\cdot \textit{Chemicals known to cause reproductive toxicity for females:} \\$

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- · Carcinogenic categories
- · EPA (Environmental Protection Agency)

CAS: 7783-06-4 Hydrogen Sulfide

I

· TLV (Threshold Limit Value)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



GHS05

- · Signal word Danger
- · Hazard-determining components of labeling:
- 2-Aminoethanol (Monoethanolamine), Reagent Grade

(Contd. on page 9)

Printing date 07/25/2024 Reviewed on 07/25/2024

Trade name: 400 grains/gal CO2 and H2S in 40% v/v MDEA + 5% v/v MEA

(Contd. of page 8)

· Hazard statements

Causes skin irritation.

Causes serious eye damage.

· Precautionary statements

Wash thoroughly after handling.

Wear protective gloves / eye protection / face protection.

If on skin: Wash with plenty of water.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:

Date of Preparation / Last Revision:

· Date of preparation / last revision

Revision 1.2 07/25/2024: Reviewed SDS for accuracy. MH/STN

Revision 0.0, 05-29-2024: Creation date for SDS. STN

07/25/2024 / 1.1

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Skin Irritation 2: Skin corrosion/irritation – Category 2

Eye Damage 1: Serious eye damage/eye irritation - Category 1

* * Data compared to the previous version altered.