Printing date 07/25/2024 Reviewed on 07/25/2024

#### 1 Identification

· Product identifier

· Trade name: 4,000 grains/gal H<sub>2</sub>S in 40% v/v MDEA

· Article number: AM450

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586

· Information department:

Technical Coordinator

Sherman Nelson shermann@aquasolutions.org

· Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666



\*

### 2 Hazard(s) identification

· Classification of the substance or mixture



Eye Irritation 2A H319 Causes serious eye irritation.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



- · Signal word Warning
- · Hazard statements

Causes serious eye irritation.

· Precautionary statements

Wash thoroughly after handling.

Wear eye protection / face protection.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3 Fire = 1Reactivity = 0

(Contd. on page 2)

(Contd. of page 1)

## Safety Data Sheet acc. to OSHA HCS

Printing date 07/25/2024 Reviewed on 07/25/2024

Trade name: 4,000 grains/gal H<sub>2</sub>S in 40% v/v MDEA

· HMIS-ratings (scale 0 - 4)

HEALTH 3 Health = 3FIRE 1 Fire = 1REACTIVITY 0 Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · **vPvB**: Not applicable.

#### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

Description. 112 water of the substances tisted beton with horning additions.		
· Dangerous components:		
CAS: 105-59-9	N-Methyldiethanolamine, 99%	40.898%
CAS: 7783-06-4	Hydrogen Sulfide	6.746%
· Table of Nonhazardous Ingredients		
CAS: 7732-18-5	Water	52.356%

### 4 First-aid measures

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

#### 6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- · Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

(Contd. on page 3)

Printing date 07/25/2024 Reviewed on 07/25/2024

Trade name: 4,000 grains/gal H<sub>2</sub>S in 40% v/v MDEA

(Contd. of page 2)

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:		
CAS: 7783-06-4	Hydrogen Sulfide	0.51 ppm
· PAC-2:		
CAS: 7783-06-4	Hydrogen Sulfide	27 ppm
· PAC-3:		
CAS: 7783-06-4	Hydrogen Sulfide	50 ppm

### 7 Handling and storage

- · Handling:
- · Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

### 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

CAS.	CAS: 7783-06-4 Hydrogen Sulfide	
	Ceiling limit value: 20; 50* ppm *10-min peak; once per 8-hr shift	
REL	Ceiling limit value: 15* mg/m³, 10* ppm *10-min	
TLV	Short-term value: 5 ppm Long-term value: 1 ppm	

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

(Contd. on page 4)

Printing date 07/25/2024 Reviewed on 07/25/2024

Trade name: 4,000 grains/gal H<sub>2</sub>S in 40% v/v MDEA

(Contd. of page 3)

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

- · Breathing equipment: Not required.
- · Protection of hands:



#### Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· **Body protection:** Protective work clothing

#### 9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information

· Appearance:

Form: Liquid

Color: Clear green-yellow

· Odor: Pungent

· Odor threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range:Undetermined.Boiling point/Boiling range:100 °C (212 °F)

• Flash point:  $100 \, ^{\circ}C \, (212 \, ^{\circ}F)$ 

· Flammability (solid, gaseous): Not applicable.

· Auto igniting: 265 °C (509 °F)

· Decomposition temperature: Not determined.

• Ignition temperature: Product is not selfigniting.

· Danger of explosion: Product does not present an explosion hazard.

(Contd. on page 5)

Printing date 07/25/2024 Reviewed on 07/25/2024

Trade name: 4,000 grains/gal H<sub>2</sub>S in 40% v/v MDEA

		(Contd. of page
· Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
· Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
· Density at 20 °C (68 °F):	0.94815 g/cm³ (7.91231 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Fully miscible.	
· Partition coefficient (n-octanol/wate	e <b>r):</b> Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Water:	52.4 %	
VOC content:	0.00 %	
	0.0 g/l / 0.00 lb/gal	
Solids content:	0.0 %	
· Other information	No further relevant information available.	

### 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Inhalative LC50/4h 1,482 mg/l

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

(Contd. on page 6)

Printing date 07/25/2024 Reviewed on 07/25/2024

Trade name: 4,000 grains/gal H<sub>2</sub>S in 40% v/v MDEA

(Contd. of page 5)

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

### 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

#### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

1 4 77	•			
	ransport	- TW 17	arman	700
	IUUSPUII	UUUU	) I III uu	uvu

•	UIV-I	vumver	

· **DOT**, **IMDG**, **IATA** UN3287

· UN proper shipping name

• **DOT** Toxic liquid, inorganic, n.o.s. (Hydrogen Sulfide)

· IMDG, IATA TOXIC LIQUID, INORGANIC, N.O.S. (Hydrogen Sulfide)

(Contd. on page 7)

Printing date 07/25/2024 Reviewed on 07/25/2024

Trade name: 4,000 grains/gal H<sub>2</sub>S in 40% v/v MDEA

	(Contd. of page
Transport hazard class(es)	
DOT	
TOXIC	
Class	6.1 Toxic substances
Label	6.1
IMDG, IATA	
Class	6.1 Toxic substances
Label	6.1
Packing group DOT, IMDG, IATA	II
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Toxic substances
Hazard identification number (Kemler code).	
EMS Number:	F- $A$ , $S$ - $A$
Stowage Category	A
Stowage Code	SW2 Clear of living quarters.
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 60 L
~ ,	On cargo aircraft only: 220 L
IMDG	
Limited quantities (LQ)	5L
Excepted quantities $(\widetilde{EQ})$	Code: E1
<del>-</del>	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 3287 TOXIC LIQUID, INORGANIC, N.O.S. (HYDROGE SULFIDE), 6.1, II

### 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara
- · Section 355 (extremely hazardous substances):

CAS: 7783-06-4 Hydrogen Sulfide

(Contd. on page 8)

Printing date 07/25/2024 Reviewed on 07/25/2024

Trade name: 4,000 grains/gal H<sub>2</sub>S in 40% v/v MDEA

(Contd. of page 7) · Section 313 (Specific toxic chemical listings): CAS: 7783-06-4 Hydrogen Sulfide · TSCA (Toxic Substances Control Act): Water **ACTIVE** N-Methyldiethanolamine, 99% **ACTIVE** Hydrogen Sulfide *ACTIVE* · Hazardous Air Pollutants None of the ingredients is listed. · Proposition 65 · Chemicals known to cause cancer: None of the ingredients is listed. · Chemicals known to cause reproductive toxicity for females: None of the ingredients is listed. · Chemicals known to cause reproductive toxicity for males: None of the ingredients is listed. · Chemicals known to cause developmental toxicity: None of the ingredients is listed. · Carcinogenic categories · EPA (Environmental Protection Agency) CAS: 7783-06-4 Hydrogen Sulfide Ι

· TLV (Threshold Limit Value)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



- · Signal word Warning
- · Hazard statements

Causes serious eye irritation.

· Precautionary statements

Wash thoroughly after handling.

Wear eye protection / face protection.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

Printing date 07/25/2024 Reviewed on 07/25/2024

Trade name: 4,000 grains/gal H<sub>2</sub>S in 40% v/v MDEA

(Contd. of page 8)

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:

Date of Preparation / Last Revision:

· Date of preparation / last revision

Revision 1.2 07/25/2024: Reviewed SDS for accuracy. MH/STN

Revision 0.0, 05-29-2024: Creation date for SDS. STN

07/25/2024 / 1.1

#### · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

\* Data compared to the previous version altered.

US