Printing date 06/06/2024 Reviewed on 06/06/2024

1 Identification

· Product identifier

· Trade name: 5.0 mg/L QA Check Standard

· Article number: HON108

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586

· Information department:

Technical Coordinator

Sherman Nelson shermann@aquasolutions.org

• Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666



*

2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.



Skin Corrosion 1A

H314 Causes severe skin burns and eye damage.

Eye Damage 1

H318 Causes serious eye damage.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS05

GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

Hydrochloric Acid

· Hazard statements

Causes severe skin burns and eye damage.

May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

Do not breathe dusts or mists.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

(Contd. on page 2)

Printing date 06/06/2024 Reviewed on 06/06/2024

Trade name: 5.0 mg/L QA Check Standard

(Contd. of page 1)

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Get medical advice/attention if you feel unwell.

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3 Fire = 0Reactivity = 0

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.

· Dangerous components:

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

CAS: 7647-01-0	Hydrochloric Acid	2.5%
CAS: 7697-37-2	Nitric Acid	0.148%
· Table of Nonhaza	urdous Ingredients	
CAS: 7732-18-5	Water	97.342%
CAS: 13477-34-4	Calcium Nitrate Tetrahydrate	0.003%
CAS: 6834-92-0	Sodium Silicate, Meta	0.002%
CAS: 7783-20-2	Ammonium Sulfate	0.002%
CAS: 10099-74-8	Lead Nitrate	0.001%
CAS: 7439-89-6	Iron Metal	0.001%
CAS: 7439-95-4	Magnesium	0.0005%
CAS: 7439-97-6	Mercury	0.0005%
CAS: 7440-36-0	Antimony Metal	0.001%
CAS: 7440-38-2	arsenic	0.0005%

- II

Printing date 06/06/2024 Reviewed on 06/06/2024

Trade name: 5.0 mg/L QA Check Standard

(Contd. of page 2)

4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Dilute with plenty of water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

Trottettire riction e.		
· PAC-1:		
CAS: 7647-01-0 H	Iydrochloric Acid	1.8 ppm
CAS: 7697-37-2 N	litric Acid	0.16 ppm
CAS: 13477-34-4 C	Calcium Nitrate Tetrahydrate	12 mg/m³
CAS: 6834-92-0 S	odium Silicate, Meta	3.8 mg/m³
CAS: 7783-20-2 A	mmonium Sulfate	13 mg/m³
CAS: 10099-74-8 L	ead Nitrate	$0.24 \ mg/m^3$
CAS: 7439-89-6 II	ron Metal	3.2 mg/m³
		(Contd. on page 4

(Contd. on page 4)

Printing date 06/06/2024 Reviewed on 06/06/2024

Trade name: 5.0 mg/L QA Check Standard

CAS: 7439-95-4	Magnesium	(Contd. of pag 18 mg/m ³
CAS: 7439-97-6	Mercury	0.15 mg/r
CAS: 7440-36-0	Antimony Metal	1.5 mg/m
CAS: 7440-38-2	arsenic	1.5 mg/m
CAS: 87-69-4	L-Tartaric Acid	1.6 mg/m
PAC-2:		- I
CAS: 7647-01-0	Hydrochloric Acid	22 ppm
CAS: 7697-37-2	Nitric Acid	24 ppm
CAS: 13477-34-4	Calcium Nitrate Tetrahydrate	130 mg/i
CAS: 6834-92-0	Sodium Silicate, Meta	42 mg/m
CAS: 7783-20-2	Ammonium Sulfate	140 mg/s
CAS: 10099-74-8	Lead Nitrate	180 mg/i
CAS: 7439-89-6	Iron Metal	35 mg/m
CAS: 7439-95-4	Magnesium	200 mg/i
CAS: 7439-97-6	Mercury	1.7 mg/n
CAS: 7440-36-0	Antimony Metal	13 mg/m
CAS: 7440-38-2	arsenic	17 mg/m
CAS: 87-69-4	L-Tartaric Acid	17 mg/m
<i>PAC-3:</i>		
CAS: 7647-01-0	Hydrochloric Acid	100 ppm
CAS: 7697-37-2	Nitric Acid	92 ppm
CAS: 13477-34-4	Calcium Nitrate Tetrahydrate	770 mg/m ³
CAS: 6834-92-0	Sodium Silicate, Meta	250 mg/m ³
CAS: 7783-20-2	Ammonium Sulfate	840 mg/m ³
CAS: 10099-74-8	Lead Nitrate	1,100 mg/1
CAS: 7439-89-6	Iron Metal	150 mg/m ²
CAS: 7439-95-4	Magnesium	1,200 mg/1
CAS: 7439-97-6	Mercury	8.9 mg/m³
CAS: 7440-36-0	Antimony Metal	80 mg/m³
CAS: 7440-38-2	arsenic	100 mg/m ³
CAS: 87-69-4	L-Tartaric Acid	100 mg/m ²

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage.
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.

(Contd. on page 5)

Printing date 06/06/2024 Reviewed on 06/06/2024

Trade name: 5.0 mg/L QA Check Standard

· Specific end use(s) No further relevant information available.

(Contd. of page 4)

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters

· Components with limit values that require monitoring at the workplace:				
CAS: 7647-01-0 Hydrochloric Acid				
NIOSH RECOMENDED EXP LIMI	Ceiling limit value: 7.0 mg/m³ mg/m³			
PEL	Ceiling limit value: 7 mg/m³, 5 ppm			
REL	Ceiling limit value: 7 mg/m³, 5 ppm			
TLV	Ceiling limit value: 2 ppm			
	A4			
CAS: 7697-37-2 Nitric Acid	CAS: 7697-37-2 Nitric Acid			
PEL	Long-term value: 5 mg/m³, 2 ppm			
REL	Short-term value: 10 mg/m³, 4 ppm			
	Long-term value: 5 mg/m³, 2 ppm			
TLV	Short-term value: (4) NIC-0.025* ppm			
	Long-term value: (2) ppm *inh. fraction + vapor, NIC-A4			
	um. fraction + vapor, MC-A4			

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

Printing date 06/06/2024 Reviewed on 06/06/2024

Trade name: 5.0 mg/L QA Check Standard

· Eye protection:

(Contd. of page 5)



Tightly sealed goggles

· Body protection: Protective work clothing

Information on basic physical and c	hemical properties	
General Information		
Appearance:	Y	
Form:	Liquid	
Color:	Colorless	
Odor:	Odorless	
Odor threshold:	Not determined.	
pH-value at 20 °C (68 °F):	<2	
Change in condition		
Melting point/Melting range:	0 °C (32 °F)	
Boiling point/Boiling range:	100 °C (212 °F)	
Flash point:	Not applicable.	
Flammability (solid, gaseous):	Not applicable.	
Decomposition temperature:	Not determined.	
Ignition temperature:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
Density at 20 °C (68 °F):	1.00516 g/cm³ (8.38806 lbs/gal)	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Fully miscible.	
Partition coefficient (n-octanol/water	r): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Water:	97.3 %	
VOC content:	0.00 %	
	0.0 g/l / 0.00 lb/gal	
Solids content:	0.0 %	

Printing date 06/06/2024 Reviewed on 06/06/2024

Trade name: 5.0 mg/L QA Check Standard

(Contd. of page 6)

· Other information

No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Inhalative LC50/4h 2,028 mg/l

- Primary irritant effect:
- · on the skin: Strong caustic effect on skin and mucous membranes.
- · on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (Internation	nal Agency for Research on Cancer)	
CAS: 10099-74-8	Lead Nitrate	2 <i>A</i>
CAS: 7439-97-6	Mercury	3
CAS: 7440-38-2	arsenic	1
· NTP (National Toxicology Program)		
CAS: 10099-74-8	Lead Nitrate	R
CAS: 7440-38-2	arsenic	K
· OSHA-Ca (Occupational Safety & Health Administration)		
CAS: 7440-38-2	arsenic	

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.

(Contd. on page 8)

Printing date 06/06/2024 Reviewed on 06/06/2024

Trade name: 5.0 mg/L QA Check Standard

(Contd. of page 7)

- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Not hazardous for water.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Rinse off of bigger amounts into drains or the aquatic environment may lead to decreased pH-values. A low pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably increased, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

Transport information		
UN-Number DOT, ADN, IMDG, IATA	Not regulated	
UN proper shipping name DOT, ADN, IMDG, IATA	Not regulated	
Transport hazard class(es)		
DOT, ADN, IMDG, IATA Class	Not regulated	
Packing group DOT, IMDG, IATA	Not regulated	
Environmental hazards:	Not applicable.	
Special precautions for user	Not applicable.	
Transport in bulk according to Annex MARPOL73/78 and the IBC Code	II of Not applicable.	
UN "Model Regulation":	Not regulated	

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

(Contd. on page 9)

Printing date 06/06/2024 Reviewed on 06/06/2024

Trade name: 5.0 mg/L QA Check Standard

Sara		(Contd. of page
	mely hazardous substances):	
CAS: 7697-37-2 I	-	
	fic toxic chemical listings):	
	Nitric Acid	
	Calcium Nitrate Tetrahydrate	
	Ammonium Sulfate	
CAS: 10099-74-8	· ·	
CAS: 7439-97-6		
	Antimony Metal	
	arsenic	
	tances Control Act):	
Water	unites Comion Act).	ACTIV
Hydrochloric Acid		ACTIV
Nitric Acid		ACTIV
Sodium Silicate, M	Tota	ACTIV
Ammonium Sulfate		ACTIV
Lead Nitrate		ACTIV
Iron Metal		ACTIV
Magnesium		ACTIV
Mercury		ACTIV
Antimony Metal		ACTIV
arsenic		ACTIV
L-Tartaric Acid		ACTIV
Hazardous Air Po	Hutante	
	Hydrochloric Acid	
CAS: 10099-74-8	•	
Proposition 65	Leau Miran	
Chemicals known	to cause cancer:	
CAS: 10099-74-8		
	arsenic	
Chemicals known	to cause reproductive toxicity for females:	
None of the ingrea		
None of the ingrea	to cause reproductive toxicity for males:	
	to cause developmental toxicity:	
CAS: 7439-97-6 A	Aercury	
Carcinogenic cate	gories	
EPA (Environmen	tal Protection Agency)	
CAS: 10099-74-8	Lead Nitrate	В
CAS: 7439-97-6	Mercury	L
C/15. 7437-77-0	ž	

Printing date 06/06/2024 Reviewed on 06/06/2024

Trade name: 5.0 mg/L QA Check Standard

(Contd. of page 9)

· TLV (Threshold Limit Value)		
CAS: 10099-74-8	Lead Nitrate	A3
CAS: 7439-97-6	Mercury	A4
CAS: 7440-38-2	arsenic	A1
· NIOSH-Ca (National Institute for Occupational Safety and Health)		

H-Ca (National Institute for Occupational Safety ana Heaun)

CAS: 7440-38-2 arsenic

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS05 GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

Hydrochloric Acid

· Hazard statements

Causes severe skin burns and eye damage.

May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

Do not breathe dusts or mists.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing, Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Get medical advice/attention if you feel unwell.

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:

Date of Preparation / Last Revision:

· Date of preparation / last revision

Revision 1.2, 06/05/2024: Reviewed SDS for accuracy. MH/STN

Revision 0.0, 05-29-2024: Creation date for SDS. STN

06/06/2024

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

(Contd. on page 11)

(Contd. of page 10)

Safety Data Sheet acc. to OSHA HCS

Printing date 06/06/2024 Reviewed on 06/06/2024

Trade name: 5.0 mg/L QA Check Standard

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Skin Corrosion 1A: Skin corrosion/irritation – Category 1A Eye Damage 1: Serious eye damage/eye irritation – Category 1

Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) - Category 2

* Data compared to the previous version altered.