Printing date 05/21/2024

Reviewed on 05/21/2024

• Trade name: <u>BCSP Tan Solvent</u> (Anhydrous)	
• Article number: MOB084	
• Details of the supplier of the safety data sheet • Manufacturer/Supplier:	
Aqua Solutions, Inc.	
6913 Highway 225	SOLUTIONS
DEER PARK, TX 77536 USA	
800-256-2586	
Information department:	
Technical Coordinator Sherman Nelson shermann@aquasolutions.org	
• Emergency telephone number:	
Chemtrec: 800-424-9300	
Canutec: 613-996-6666	
P Hazard(s) identification	
· Classification of the substance or mixture	
GHS02 Flame	
GHS02 Flame Flammable Liquids 2	H225 Highly flammable liquid and vapor.
	H225 Highly flammable liquid and vapor.
Flammable Liquids 2	H225 Highly flammable liquid and vapor. H361 Suspected of damaging fertility or the unborn child
Flammable Liquids 2 GHS08 Health hazard Toxic to Reproduction 2	
Flammable Liquids 2 GHS08 Health hazard Toxic to Reproduction 2	H361 Suspected of damaging fertility or the unborn child H373 May cause damage to organs through prolonged of
Flammable Liquids 2 GHS08 Health hazard Toxic to Reproduction 2 Specific Target Organ Toxicity - Repeated Exposure 2	H361 Suspected of damaging fertility or the unborn child H373 May cause damage to organs through prolonged repeated exposure.
Flammable Liquids 2 GHS08 Health hazard Toxic to Reproduction 2 Specific Target Organ Toxicity - Repeated Exposure 2 Aspiration Hazard 1 GHS07	H361 Suspected of damaging fertility or the unborn child H373 May cause damage to organs through prolonged repeated exposure. H304 May be fatal if swallowed and enters airways.
Flammable Liquids 2 GHS08 Health hazard Toxic to Reproduction 2 Specific Target Organ Toxicity - Repeated Exposure 2 Aspiration Hazard 1 GHS07 Skin Irritation 2	<ul> <li>H361 Suspected of damaging fertility or the unborn child</li> <li>H373 May cause damage to organs through prolonged or repeated exposure.</li> <li>H304 May be fatal if swallowed and enters airways.</li> <li>H315 Causes skin irritation.</li> </ul>
Flammable Liquids 2 GHS08 Health hazard Toxic to Reproduction 2 Specific Target Organ Toxicity - Repeated Exposure 2 Aspiration Hazard 1 GHS07	H361 Suspected of damaging fertility or the unborn child H373 May cause damage to organs through prolonged repeated exposure. H304 May be fatal if swallowed and enters airways.

(Contd. on page 2)

Printing date 05/21/2024

Trade name: BCSP Tan Solvent (Anhydrous) Reviewed on 05/21/2024

· Signal word Danger	(Contd. of page 1
· Hazard-determining components of labeling:	
Toluene	
Isopropanol	
· Hazard statements	
Highly flammable liquid and vapor.	
Causes skin irritation.	
Causes serious eye irritation.	
Suspected of damaging fertility or the unborn child.	
May cause drowsiness or dizziness.	
May cause damage to organs through prolonged or repeated exposure.	
May be fatal if swallowed and enters airways.	
Precautionary statements	
Obtain special instructions before use.	
Do not handle until all safety precautions have been read and understood.	
Keep away from heat/sparks/open flames/hot surfaces No smoking.	
Ground/bond container and receiving equipment.	
Use explosion-proof electrical/ventilating/lighting/equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Do not breathe dust/fume/gas/mist/vapors/spray.	
Wash thoroughly after handling.	
Use only outdoors or in a well-ventilated area.	
Wear protective gloves/protective clothing/eye protection/face protection.	
If swallowed: Immediately call a poison center/doctor.	
Specific treatment (see on this label).	
Do NOT induce vomiting.	
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with wa	ter/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses,	if present and easy to do
Continue rinsing.	
IF exposed or concerned: Get medical advice/attention.	
Call a poison center/doctor if you feel unwell.	
Get medical advice/attention if you feel unwell.	
Take off contaminated clothing and wash it before reuse.	
If skin irritation occurs: Get medical advice/attention.	
If eye irritation persists: Get medical advice/attention.	
In case of fire: Use CO2, powder or water spray to extinguish.	
Store in a well-ventilated place. Keep container tightly closed.	
Store in a well-ventilated place. Keep cool.	
Store locked up.	
Dispose of contents/container in accordance with local/regional/national/international	regulations.
Classification system:	
NFPA ratings (scale 0 - 4)	
Health = 2	
Fire = $3$	
2 $0$ Reactivity = 0	
HMIS-ratings (scale 0 - 4)	
$\frac{\text{HEALTH}}{2} Health = 2$	
FIRE 3 Fire = 3	
<b>REACTIVITY</b> $O$ Reactivity = 0	
	(Contd. on page 3

- US

Printing date 05/21/2024

Reviewed on 05/21/2024

#### Trade name: BCSP Tan Solvent (Anhydrous)

(Contd. of page 2)

#### · Other hazards

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

#### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- Description: Mixture of the substances listed below with nonhazardous additions.

#### · Dangerous components:

0	*	
CAS: 108-88-3	Toluene	52.477%
CAS: 67-63-0	Isopropanol	47.523%

#### **4** First-aid measures

· Description of first aid measures

- General information:
- Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

## **5** Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. • For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.

· Advice for firefighters

· Protective equipment: Mouth respiratory protective device.

#### **6** Accidental release measures

- Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.
- Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 4)

Printing date 05/21/2024

Reviewed on 05/21/2024

Trade name: BCSP Tan Solvent (Anhydrous)

Dispose contam	inated material as waste according to section 13.	(Contd. of page
Ensure adequat	0	
$\cdot Reference to other the second sec$		
See Section 7 fo	r information on safe handling.	
See Section 8 fo	r information on personal protection equipment.	
See Section 13 f	or disposal information.	
· Protective Actio	n Criteria for Chemicals	
· PAC-1:		
CAS: 108-88-3	Toluene	67 ppm
CAS: 67-63-0	Isopropanol	400 ppm
· PAC-2:		
CAS: 108-88-3	Toluene	560 ppm
CAS: 67-63-0	Isopropanol	2000* ppm
· PAC-3:		
CAS: 108-88-3	Toluene	3700* ppm
CAS: 67-63-0	Isopropanol	12000** ppm

#### 7 Handling and storage

· Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed. Store in cool, dry conditions in well sealed receptacles.
- Store in cool, ary conditions in well sealed receptacies.
- Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see section 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

#### CAS: 108-88-3 Toluene

PEL Long-term value: 200 ppm Ceiling limit value: 300; 500\* ppm \*10-min peak per 8-hr shift

(Contd. on page 5)

US ·

Printing date 05/21/2024

Reviewed on 05/21/2024

Trade name: BCSP Tan Solvent (Anhydrous)

	(Contd. of page 4)
REL	Short-term value: 560 mg/m <sup>3</sup> , 150 ppm
	Long-term value: 375 mg/m³, 100 ppm
TLV	Long-term value: 20 ppm BEI, OTO, A4
CAS	: 67-63-0 Isopropanol
PEL	Long-term value: 980 mg/m <sup>3</sup> , 400 ppm
REL	Short-term value: 1225 mg/m³, 500 ppm Long-term value: 980 mg/m³, 400 ppm
TLV	Short-term value: 400 ppm Long-term value: 200 ppm BEI, A4
· Ingr	edients with biological limit values:
CAS	: 108-88-3 Toluene
BEI	0.02 mg/L LD50 Intraperitoneal: blood Time: prior to last shift of workweek LD50: Toluene
	0.03 mg/L LD50 Intraperitoneal: urine Time: end of shift LD50: Toluene
	0.3 mg/g creatinine LD50 Intraperitoneal: urine Time: end of shift LD50: o-Cresol with hydrolysis (background)
CAS	: 67-63-0 Isopropanol
BEI	40 mg/L LD50 Intraperitoneal: urine Time: end of shift at end of workweek LD50: Acetone (background, nonspecific)
· Add	itional information: The lists that were valid during the creation were used as basis.
· Pers · Gen Keep Imm Was. Stor Avoi · Brea In co resp.	onal protective equipment: eral protective and hygienic measures: o away from foodstuffs, beverages and feed. ediately remove all soiled and contaminated clothing. h hands before breaks and at the end of work. e protective clothing separately. d contact with the eyes and skin. thing equipment: use of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use iratory protective device that is independent of circulating air. ection of hands: Protective gloves
	(Contd. on page 6)

US

Printing date 05/21/2024

Reviewed on 05/21/2024

Trade name: BCSP Tan Solvent (Anhydrous)

(Contd. of page 5)

US

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation • Material of gloves

# The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

Information on basic physical and c General Information	chemical properties
Appearance:	
Form:	Liquid
Color:	Clear
Odor:	Organic
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
<b>Boiling point/Boiling range:</b>	82 °C (179.6 °F)
Flash point:	4 °C (39.2 °F)
Flammability (solid, gaseous):	Highly flammable.
Auto igniting:	425 °C (797 °F)
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
Explosion limits:	
Lower:	1.2 Vol %
Upper:	12 Vol %
Vapor pressure at 20 °C (68 °F):	43 hPa (32.3 mm Hg)
Density at 20 °C (68 °F):	0.82591 g/cm <sup>3</sup> (6.89222 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.

Printing date 05/21/2024

Reviewed on 05/21/2024

Trade name: BCSP Tan Solvent (Anhydrous)

		(Contd. of page
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/v	vater): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	100.0 %	
VOC content:	100.00 %	
	825.9 g/l / 6.89 lb/gal	
Solids content:	0.0 %	
• Other information	No further relevant information available.	

## **10 Stability and reactivity**

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

## **11** Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: Irritating effect.
- Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

#### · Carcinogenic categories

· IARC (International Agency for Research on Cancer)

All components have the value 3.

· NTP (National Toxicology Program)

None of the ingredients is listed.

#### · OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

(Contd. on page 8)

*Printing date 05/21/2024* 

Reviewed on 05/21/2024

Trade name: BCSP Tan Solvent (Anhydrous)

(Contd. of page 7)

## **12** Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:
- Water hazard class 2 (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

#### **13 Disposal considerations**

- · Waste treatment methods
- *Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.*
- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

UN-Number DOT, IMDG, IATA	UN1993
UN proper shipping name DOT	Flammable liquids, n.o.s. (Toluene, Isopropanol
IMDG, IATA	) FLAMMABLE LIQUID, N.O.S. (Toluene, Isopropanol )
Transport hazard class(es)	
DOT	
P.MMARE LOOD	
Class	3 Flammable liquids

Printing date 05/21/2024

Reviewed on 05/21/2024

Trade name: BCSP Tan Solvent (Anhydrous)

	(Contd. of page
Label	3
IMDG, IATA	
Class	3 Flammable liquids
Label	3
Packing group	
DOT, IMDG, IATA	II
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids
Hazard identification number (Kemler code):	
EMS Number: Stowage Category	<i>F-E,<u>S-E</u> B</i>
0 01	D
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L
	On cargo aircraft only: 60 L
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (TOLUEN ISOPROPANOL ), 3, II

# **15 Regulatory information**

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available. • Sara

· Section 355 (extremely hazardous substances):	
None of the ingredients is listed.	
· Section 313 (Specific toxic chemical listings):	
All ingredients are listed.	
· TSCA (Toxic Substances Control Act):	
Toluene	ACTIVE
Isopropanol	ACTIVE
(Conto	l. on page 10)

*Printing date 05/21/2024* 

Reviewed on 05/21/2024

Trade name: BCSP Tan Solvent (Anhydrous)

(Contd. of page 9)

II

· Hazardous Air Pollutants

CAS: 108-88-3 Toluene

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

 $\cdot$  Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

CAS: 108-88-3 Toluene

· Carcinogenic categories

· EPA (Environmental Protection Agency)

CAS: 108-88-3 Toluene

· TLV (Threshold Limit Value)

All components have the value A4.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms* 



· Signal word Danger

· Hazard-determining components of labeling: Toluene Isopropanol · Hazard statements Highly flammable liquid and vapor. Causes skin irritation. Causes serious eye irritation. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways. · Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray.

Printing date 05/21/2024

Reviewed on 05/21/2024

#### Trade name: BCSP Tan Solvent (Anhydrous)

(Contd. of page 10) Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Immediately call a poison center/doctor. Specific treatment (see on this label). Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. *Call a poison center/doctor if you feel unwell.* Get medical advice/attention if you feel unwell. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• Department issuing SDS: Environment protection department.

 Contact: Date of Preparation / Last Revision:
 Date of preparation / last revision Revision 1.2, 05/21/2024: Reviewed SDS for accuracy. MH/STN Creation date for SDS 12-03-2015. STN 05/21/2024

· Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit **REL:** Recommended Exposure Limit BEI: Biological Exposure Limit Flammable Liquids 2: Flammable liquids – Category 2 Skin Irritation 2: Skin corrosion/irritation – Category 2 Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A Toxic to Reproduction 2: Reproductive toxicity – Category 2 Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3

(Contd. on page 12)

<sup>—</sup> U

Printing date 05/21/2024

Trade name: BCSP Tan Solvent (Anhydrous) Reviewed on 05/21/2024

(Contd. of page 11)

Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2 Aspiration Hazard 1: Aspiration hazard – Category 1 • \* Data compared to the previous version altered.

US