

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/06/2024

Reviewed on 06/06/2024

1 Identification

- **Product identifier**
- **Trade name:** 3.0 mg/kg S-21 CCV Check Std.
in 10:90 Oil/Xylene
- **Article number:** SH076
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Aqua Solutions, Inc.
6913 Highway 225
DEER PARK, TX 77536
USA
800-256-2586
- **Information department:**
Technical Coordinator
Sherman Nelson shermann@aquasolutions.org
- **Emergency telephone number:**
Chemtrec: 800-424-9300
Canutec: 613-996-6666



2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 3 H226 Flammable liquid and vapor.



GHS07

Acute Toxicity - Dermal 4 H312 Harmful in contact with skin.
Acute Toxicity - Inhalation 4 H332 Harmful if inhaled.
Skin Irritation 2 H315 Causes skin irritation.

- **Label elements**

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS07

- **Signal word** Warning

- **Hazard-determining components of labeling:**

Xylene (Xylol)

- **Hazard statements**

Flammable liquid and vapor.

Harmful in contact with skin or if inhaled.

Causes skin irritation.

- **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/06/2024

Reviewed on 06/06/2024

**Trade name: 3.0 mg/kg S-21 CCV Check Std.
in 10:90 Oil/Xylene**

(Contd. of page 1)

Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing dust/fume/gas/mist/vapors/spray
Wash thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Call a poison center/doctor if you feel unwell.
Specific treatment (see on this label).
Take off contaminated clothing and wash it before reuse.
If skin irritation occurs: Get medical advice/attention.
In case of fire: Use CO₂, powder or water spray to extinguish.
Store in a well-ventilated place. Keep cool.
Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 1330-20-7	Xylene (Xylol)	89.928%
----------------	----------------	---------

· **Table of Nonhazardous Ingredients**

CAS: 8042-47-5	White mineral oil, petroleum	>10.016%
CAS: 100-00-0	Proprietary, non-hazardous material	<0.05%
CAS: 7440-02-0	nickel powder	<0.003%
CAS: 7440-43-9	cadmium Metal	<0.003%

US

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/06/2024

Reviewed on 06/06/2024

**Trade name: 3.0 mg/kg S-21 CCV Check Std.
in 10:90 Oil/Xylene**

(Contd. of page 2)

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

- **PAC-1:**

CAS: 1330-20-7	Xylene (Xylol)	130 ppm
CAS: 7440-43-9	cadmium Metal	0.10 mg/m ³

- **PAC-2:**

CAS: 1330-20-7	Xylene (Xylol)	920* ppm
CAS: 7440-43-9	cadmium Metal	0.76 mg/m ³

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/06/2024

Reviewed on 06/06/2024

**Trade name: 3.0 mg/kg S-21 CCV Check Std.
in 10:90 Oil/Xylene**

(Contd. of page 3)

· **PAC-3:**

CAS: 1330-20-7	Xylene (Xylol)	2500* ppm
CAS: 7440-43-9	cadmium Metal	4.7 mg/m ³

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

CAS: 1330-20-7 Xylene (Xylol)	
PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Long-term value: 20 ppm BEI, A4

· **Ingredients with biological limit values:**

CAS: 1330-20-7 Xylene (Xylol)	
BEI	1.5 g/g creatinine LD50 Intraperitoneal: urine Time: end of shift LD50: Methylhippuric acids

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the skin.
Avoid contact with the eyes and skin.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/06/2024

Reviewed on 06/06/2024

**Trade name: 3.0 mg/kg S-21 CCV Check Std.
in 10:90 Oil/Xylene**

(Contd. of page 4)

- **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

- **Body protection:** Protective work clothing

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form:	Liquid
Color:	Clear
Odor:	Organic
Odor threshold:	Not determined.

- **pH-value:** Not determined.

- **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	36 °C (96.8 °F)

- **Flash point:** 30 °C (86 °F)

- **Flammability (solid, gaseous):** Flammable.

- **Auto igniting:** 500 °C (932 °F)

- **Decomposition temperature:** Not determined.

- **Ignition temperature:** Product is not selfigniting.

- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/06/2024

Reviewed on 06/06/2024

**Trade name: 3.0 mg/kg S-21 CCV Check Std.
in 10:90 Oil/Xylene**

(Contd. of page 5)

· Explosion limits:	
Lower:	1.1 Vol %
Upper:	7 Vol %
· Vapor pressure at 20 °C (68 °F):	6.7-8.2 hPa (5-6.2 mm Hg)
· Density:	Not determined.
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water at 20 °C (68 °F):	0.2 g/l
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic at 20 °C (68 °F):	0.61 mPas
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	89.9 %
VOC content:	89.93 %
	899.3 g/l / 7.50 lb/gal
Solids content:	<0.0 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

ATE (Acute Toxicity Estimate)

Dermal	LD50	1,223 mg/kg
Inhalative	LC50/4h	12.2 mg/l

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:
(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/06/2024

Reviewed on 06/06/2024

**Trade name: 3.0 mg/kg S-21 CCV Check Std.
in 10:90 Oil/Xylene**

(Contd. of page 6)

Harmful
Irritant

· **Carcinogenic categories**

· IARC (International Agency for Research on Cancer)		
CAS: 1330-20-7	Xylene (Xylol)	3
CAS: 7440-43-9	cadmium Metal	1
· NTP (National Toxicology Program)		
CAS: 7440-43-9	cadmium Metal	K
· OSHA-Ca (Occupational Safety & Health Administration)		
CAS: 7440-43-9	cadmium Metal	

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
 Water hazard class 2 (Self-assessment): hazardous for water
 Do not allow product to reach ground water, water course or sewage system.
 Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
 Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· UN-Number	
· DOT, IMDG, IATA	UN1993
· UN proper shipping name	
· DOT	Flammable liquids, n.o.s. (Xylene (Xylol))
· IMDG, IATA	FLAMMABLE LIQUID, N.O.S. (Xylene (Xylol))

(Contd. on page 8)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/06/2024

Reviewed on 06/06/2024

**Trade name: 3.0 mg/kg S-21 CCV Check Std.
in 10:90 Oil/Xylene**

(Contd. of page 7)

· **Transport hazard class(es)**

· **DOT**



· **Class** 3 Flammable liquids
 · **Label** 3

· **IMDG, IATA**



· **Class** 3 Flammable liquids
 · **Label** 3

· **Packing group**
 · **DOT, IMDG, IATA** II

· **Environmental hazards:** Not applicable.

· **Special precautions for user** Warning: Flammable liquids
 · **Hazard identification number (Kemler code):** 30
 · **EMS Number:** F-E,S-D
 · **Stowage Category** A

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **DOT**
 · **Quantity limitations** On passenger aircraft/rail: 60 L
 On cargo aircraft only: 220 L

· **IMDG**

· **Limited quantities (LQ)** 5L
 · **Excepted quantities (EQ)** Code: E1
 Maximum net quantity per inner packaging: 30 ml
 Maximum net quantity per outer packaging: 1000 ml

· **UN "Model Regulation":** UN 1993 FLAMMABLE LIQUID, N.O.S. (XYLENE (XYLOL)), 3, II

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

No further relevant information available.

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/06/2024

Reviewed on 06/06/2024

**Trade name: 3.0 mg/kg S-21 CCV Check Std.
in 10:90 Oil/Xylene**

(Contd. of page 8)

· Section 313 (Specific toxic chemical listings):		
CAS: 1330-20-7	Xylene (Xylol)	
CAS: 7440-43-9	cadmium Metal	
· TSCA (Toxic Substances Control Act):		
Xylene (Xylol)	ACTIVE	
White mineral oil, petroleum	ACTIVE	
cadmium Metal	ACTIVE	
· Hazardous Air Pollutants		
CAS: 1330-20-7	Xylene (Xylol)	
· Proposition 65		
· Chemicals known to cause cancer:		
CAS: 7440-43-9	cadmium Metal	
· Chemicals known to cause reproductive toxicity for females:		
None of the ingredients is listed.		
· Chemicals known to cause reproductive toxicity for males:		
CAS: 7440-43-9	cadmium Metal	
· Chemicals known to cause developmental toxicity:		
CAS: 7440-43-9	cadmium Metal	
· Carcinogenic categories		
· EPA (Environmental Protection Agency)		
CAS: 1330-20-7	Xylene (Xylol)	I
CAS: 7440-43-9	cadmium Metal	B1
· TLV (Threshold Limit Value)		
CAS: 1330-20-7	Xylene (Xylol)	A4
CAS: 7440-43-9	cadmium Metal	A2
· NIOSH-Ca (National Institute for Occupational Safety and Health)		
CAS: 7440-43-9	cadmium Metal	

· GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



GHS02 GHS07

· Signal word Warning

· Hazard-determining components of labeling:

Xylene (Xylol)

· Hazard statements

Flammable liquid and vapor.

Harmful in contact with skin or if inhaled.

Causes skin irritation.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/06/2024

Reviewed on 06/06/2024

**Trade name: 3.0 mg/kg S-21 CCV Check Std.
in 10:90 Oil/Xylene**

(Contd. of page 9)

Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing dust/fume/gas/mist/vapors/spray
Wash thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Call a poison center/doctor if you feel unwell.
Specific treatment (see on this label).
Take off contaminated clothing and wash it before reuse.
If skin irritation occurs: Get medical advice/attention.
In case of fire: Use CO₂, powder or water spray to extinguish.
Store in a well-ventilated place. Keep cool.
Dispose of contents/container in accordance with local/regional/national/international regulations.
· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Environment protection department.
- **Contact:**
Date of Preparation / Last Revision:
- **Date of preparation / last revision**
Revision 1.2, 06/05/2024: Reviewed SDS for accuracy. MH/STN
Revision 0.0, 05-29-2024: Creation date for SDS. STN
06/06/2024
- **Abbreviations and acronyms:**
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
BEI: Biological Exposure Limit
Flammable Liquids 3: Flammable liquids – Category 3
Acute Toxicity - Dermal 4: Acute toxicity – Category 4
Skin Irritation 2: Skin corrosion/irritation – Category 2
- *** Data compared to the previous version altered.**