Safety Data Sheet acc. to OSHA HCS

Printing date 06/06/2024

*

Reviewed on 06/06/2024

I Jour Continue		
Identification		
Product identifier		
Trade name: <u>o-Xylene, HP</u>	LC Grade	
Article number: X7519		
CAS Number:		
95-47-6		
EC number:		
202-422-2 Index number:		
601-022-00-9		SOLUTIONS
Details of the supplier of th	e safety data sheet	
Manufacturer/Supplier:		
Aqua Solutions, Inc.		
6913 Highway 225		
DEER PARK, TX 77536		
USA 800-256-2586		
Information department: Technical Coordinator		
Sherman Nelson shermann@	aquasolutions org	
Technical Coordinator	- uquusotunions.01 z	
Sherman Nelson shermann@	aquasolutions.org	
Emergency telephone numb		
Chemtrec: 800-424-9300		
Canutec: 613-996-6666		
Hazard(s) identification		
Classification of the substan		
Classification of the substan	nce or mixture	
Classification of the substan		
Classification of the substant GHS02 Flame Flammable Liquids 3	nce or mixture	
Classification of the substan	nce or mixture	
Classification of the substant GHS02 Flame Flammable Liquids 3 GHS07	nce or mixture H226 Flammable liquid and vapor.	
Classification of the substant GHS02 Flame Flammable Liquids 3 GHS07 Acute Toxicity - Dermal 4	nce or mixture H226 Flammable liquid and vapor. H312 Harmful in contact with skin.	
Classification of the substant GHS02 Flame Flammable Liquids 3 GHS07 Acute Toxicity - Dermal 4 Acute Toxicity - Inhalation 4	nce or mixture H226 Flammable liquid and vapor. H312 Harmful in contact with skin. H332 Harmful if inhaled.	
Classification of the substant GHS02 Flame Flammable Liquids 3 GHS07 Acute Toxicity - Dermal 4	nce or mixture H226 Flammable liquid and vapor. H312 Harmful in contact with skin.	
Classification of the substant GHS02 Flame Flammable Liquids 3 GHS07 Acute Toxicity - Dermal 4 Acute Toxicity - Inhalation 4 Skin Irritation 2 Label elements	nce or mixture H226 Flammable liquid and vapor. H312 Harmful in contact with skin. H332 Harmful if inhaled. H315 Causes skin irritation.	ing to the Globally Harmonized System (G
Classification of the substant GHS02 Flame Flammable Liquids 3 GHS07 Acute Toxicity - Dermal 4 Acute Toxicity - Inhalation 4 Skin Irritation 2 Label elements GHS label elements The sul	nce or mixture H226 Flammable liquid and vapor. H312 Harmful in contact with skin. H332 Harmful if inhaled. H315 Causes skin irritation.	ing to the Globally Harmonized System (G
Classification of the substant GHS02 Flame Flammable Liquids 3 GHS07 Acute Toxicity - Dermal 4 Acute Toxicity - Inhalation 4 Skin Irritation 2 Label elements GHS label elements The sul	nce or mixture H226 Flammable liquid and vapor. H312 Harmful in contact with skin. H332 Harmful if inhaled. H315 Causes skin irritation.	ing to the Globally Harmonized System (G
Classification of the substant GHS02 Flame Flammable Liquids 3 GHS07 Acute Toxicity - Dermal 4 Acute Toxicity - Inhalation 4 Skin Irritation 2 Label elements GHS label elements The sub Hazard pictograms	nce or mixture H226 Flammable liquid and vapor. H312 Harmful in contact with skin. H332 Harmful if inhaled. H315 Causes skin irritation.	ing to the Globally Harmonized System (G
Classification of the substant GHS02 Flame Flammable Liquids 3 GHS07 Acute Toxicity - Dermal 4 Acute Toxicity - Inhalation 4 Skin Irritation 2 Label elements GHS label elements The sub Hazard pictograms	nce or mixture H226 Flammable liquid and vapor. H312 Harmful in contact with skin. H332 Harmful if inhaled. H315 Causes skin irritation.	ing to the Globally Harmonized System (G
Classification of the substant GHS02 Flame Flammable Liquids 3 Construction GHS07 Acute Toxicity - Dermal 4 Acute Toxicity - Inhalation 4 Skin Irritation 2 Label elements GHS label elements The sub Hazard pictograms Construction GHS07 Signal word Warning	nce or mixture H226 Flammable liquid and vapor. H312 Harmful in contact with skin. H332 Harmful if inhaled. H315 Causes skin irritation.	ing to the Globally Harmonized System (G

Printing date 06/06/2024

*

Reviewed on 06/06/2024

Trade name: o-Xylene, HPLC Grade

	(Contd. of page 1)
Harmful in contact with skin or if inhaled.	
Causes skin irritation.	
· Precautionary statements	
Keep away from heat/sparks/open flames/hot surfaces No smoking.	
Keep container tightly closed.	
Ground/bond container and receiving equipment.	
Use explosion-proof electrical/ventilating/lighting/equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Avoid breathing dust/fume/gas/mist/vapors/spray	
Wash thoroughly after handling.	
Use only outdoors or in a well-ventilated area.	
Wear protective gloves/protective clothing/eye protection/face protection.	
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower	•
IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell.	
Specific treatment (see on this label).	
Take off contaminated clothing and wash it before reuse.	
If skin irritation occurs: Get medical advice/attention.	
In case of fire: Use CO2, powder or water spray to extinguish.	
Store in a well-ventilated place. Keep cool.	
Dispose of contents/container in accordance with local/regional/national/international regulation	15.
· Classification system:	
· NFPA ratings (scale 0 - 4)	
Health = 1 Fire = 3 Reactivity = 0	
· HMIS-ratings (scale 0 - 4)	
HEALTH1Health = 1FIRE3Fire = 3REACTIVITY $Reactivity = 0$	
• Other hazards	
• Results of PBT and vPvB assessment	
• PBT: Not applicable. • vPvB: Not applicable.	
3 Composition/information on ingredients	
· Chemical characterization: Substances	
· CAS No. Description	
CAS: 95-47-6 o-Xylene	
· Identification number(s)	
• EC number: 202-422-2	
· Index number: 601-022-00-9	
	US

(Contd. on page 3)

Printing date 06/06/2024

Reviewed on 06/06/2024

Trade name: o-Xylene, HPLC Grade

(Contd. of page 2)

4 First-aid measures

· Description of first aid measures

• General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- *Indication of any immediate medical attention and special treatment needed No further relevant information available.*

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- *Personal precautions, protective equipment and emergency procedures* Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- *Methods and material for containment and cleaning up:* Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.
- · Reference to other sections
- See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.
- · Protective Action Criteria for Chemicals
- PAC-1: Substance is not listed.
- PAC-2: Substance is not listed.
- · PAC-3: Substance is not listed.

7 Handling and storage

- · Handling:
- · Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
- Protect against electrostatic charges.

(Contd. on page 4)

US

Printing date 06/06/2024

Reviewed on 06/06/2024

Trade name: o-Xylene, HPLC Grade

(Contd. of page 3)

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- Components with limit values that require monitoring at the workplace:

CAS: 95-47-6 o-Xylene

PEL Long-term value: 435 mg/m³, 100 ppm

- REL Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm
- TLV Long-term value: 20 ppm BEI, A4

· Ingredients with biological limit values:

CAS: 95-47-6 o-Xylene

BEI 1.5 g/g creatinine LD50 Intraperitoneal: urine Time: end of shift LD50: Methylhippuric acids

• Additional information: The lists that were valid during the creation were used as basis.

- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work.
- Avoid contact with the skin.
- Avoid contact with the eyes and skin.

• Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

• Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation • Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

(Contd. on page 5)

US

Printing date 06/06/2024

Reviewed on 06/06/2024

(Contd. of page 4)

Trade name: o-Xylene, HPLC Grade

 \cdot Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



*

Tightly sealed goggles

· Body protection: Protective work clothing

Information on basic physical and o	chemical properties
General Information	nemuu propernes
Appearance:	
Form:	Liquid
Color:	Clear
Odor:	Distinct
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	-25.2 °C (-13.4 °F)
Boiling point/Boiling range:	144.4 °C (291.9 °F)
Flash point:	17-30 °C (62.6-86 °F)
Flammability (solid, gaseous):	Flammable.
Auto igniting:	465 °C (869 °F)
Decomposition temperature:	Not determined.
Ignition temperature:	Not determined.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
Explosion limits:	
Lower:	1.7 Vol %
Upper:	7.6 Vol %
Vapor pressure at 20 °C (68 °F):	6.7 hPa (5 mm Hg)
Density at 20 °C (68 °F):	0.878 g/cm ³ (7.32691 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
<i>Water at 20 °C (68 °F):</i>	0.2 g/l
Partition coefficient (n-octanol/wat	er): Not determined.
Viscosity:	
Dynamic at 20 °C (68 °F):	0.81 mPas
Kinematic:	Not determined.

US

Printing date 06/06/2024

Reviewed on 06/06/2024

(Contd. of page 5)

Trade name: o-Xylene, HPLC Grade

• Other information

No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

Dermal LD50 1,100 mg/kg (ATE)

Inhalative LC50/4h 11 mg/l (ATE)

- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: No irritating effect.
- Sensitization: No sensitizing effects known.
- · Additional toxicological information:
- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer) 3
- · NTP (National Toxicology Program) Substance is not listed.
- · OSHA-Ca (Occupational Safety & Health Administration) Substance is not listed.

12 Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- *Persistence and degradability No further relevant information available.*
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:

· General notes:

Water hazard class 2 (Assessment by list): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.

• vPvB: Not applicable.

• Other adverse effects No further relevant information available.

(Contd. on page 7)

Printing date 06/06/2024

Reviewed on 06/06/2024

Trade name: o-Xylene, HPLC Grade

(Contd. of page 6)

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

UN-Number	
DOT, IMDG, IATA	UN1307
UN proper shipping name	
DOT	Xylenes
IMDG, IATA	XYLENES
Transport hazard class(es)	
Class	3 Flammable liquids
Label	3
Class Label	3 Flammable liquids
Packing group	5
DOT, IMDG, IATA	III
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids
Hazard identification number (Kemler code)	
EMS Number:	F-E,S-D
Stowage Category	В
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L
Hazardous substance:	On cargo aircraft only: 60 L 1000 lbs, 454 kg

Printing date 06/06/2024

Reviewed on 06/06/2024

Trade name: o-Xylene, HPLC Grade

(Contd.	of	page	7)
(Contu.	or	page	''

• UN "Model Regulation":	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml UN 1307 XYLENES, 3, III	
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E2	

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara
- Section 355 (extremely hazardous substances): Substance is not listed.
- Section 313 (Specific toxic chemical listings): Substance is listed.
- TSCA (Toxic Substances Control Act): ACTIVE
- · Hazardous Air Pollutants Substance is listed.
- · Proposition 65
- · Chemicals known to cause cancer: Substance is not listed.
- · Chemicals known to cause reproductive toxicity for females: Substance is not listed.
- · Chemicals known to cause reproductive toxicity for males: Substance is not listed.
- · Chemicals known to cause developmental toxicity: Substance is not listed.
- · Carcinogenic categories
- · EPA (Environmental Protection Agency) I
- TLV (Threshold Limit Value) A4
- · NIOSH-Ca (National Institute for Occupational Safety and Health) Substance is not listed.
- GHS label elements The substance is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



· Signal word Warning

- Hazard statements
 Flammable liquid and vapor.
 Harmful in contact with skin or if inhaled.
 Causes skin irritation.
 Precautionary statements
 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- Keep container tightly closed.
- Ground/bond container and receiving equipment.
- Use explosion-proof electrical/ventilating/lighting/equipment.
- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Avoid breathing dust/fume/gas/mist/vapors/spray
- Wash thoroughly after handling.
- Use only outdoors or in a well-ventilated area.
- Wear protective gloves/protective clothing/eye protection/face protection.
- If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- IF INHALED: Remove person to fresh air and keep comfortable for breathing.

(Contd. on page 9)

Printing date 06/06/2024

Reviewed on 06/06/2024

Trade name: o-Xylene, HPLC Grade

(Contd. of page 8)

Call a poison center/doctor if you feel unwell. Specific treatment (see on this label). Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep cool. Dispose of contents/container in accordance with local/regional/national/international regulations. • Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

• Contact: Date of Preparation / Last Revision:

- Date of preparation / last revision
 Revision 1.2, 06/05/2024: Reviewed SDS for accuracy. MH/STN 06/06/2024
 Abbreviations and acronyms:
 IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transport Association
 IATA: International Air Transport Association
 EINECS: European Inventory of Existing Commercial Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flammable Liquids 3: Flammable liquids – Category 3 Acute Toxicity - Dermal 4: Acute toxicity – Category 4 Skin Irritation 2: Skin corrosion/irritation – Category 2
- * Data compared to the previous version altered.